


COMMERCIAL
SOLUTIONS



Innovative solutions for
industrial applications

Actuators and servos



CONTENT

MULTIPLEX/Hitec worldwide	6	HLS12-RS485-10050	54	DB778WP	108	MD146SH	164
Product overview	7	HLS12-RS485-30100	56	DBX961WP	110	MD70MH	166
Analogue actuators	8	HLS12-RS485-50100	58	MDB941WP-CAN	112	MD845WP	168
Digital actuators	8	HLS12-RS485-100100	60	MDB950SW-CAN	114	MD1100WP	170
Interfaces	10	HLS12-RS485-30210	62	MDB961WP-CAN	116	MDR845WP	172
Feature Overview	11	HLS12-RS485-50210	64	MDB961WP-CAN 28V	118	MD245MW-RS485	174
Series summary	13	HLS12-RS485-100210	66	MDB1200WP	120	MD250MW-RS485	176
Two-way communication (feedback)	14	HLS12-RS485-30380	68	MDB961WP	122	MD950TW-RS485	178
Motortypes Overview	15	HLS12-RS485-50380	70	MDB89MH	124	MD980TW-RS485	180
ISO Certificates	17	HLS12-RS485-100380	72	MDB-777WP-CAN/DroneCAN	126	D485HW	182
SERVO TYPES				MDB778WP-CAN/DroneCAN	128	D646WP	184
HLS12-3050, -30100, -30210, -30380	20	SG15BL-CAN (M5 Circular)	74	MDB941WP-DroneCAN	130	D954SW	186
HLS12-5050, -50100, -50210, -50380	22	SG20BL-CAN-12V (M8 Circular)	76	MDB950SW-DroneCAN	132	D951TW	188
HLS-10050, -100100, -100210, -100380	24	SG33BL-T-12V (DSUB)	78	MDB961WP-UAVCAN / DroneCAN	134	D980TW	190
HLS12-CAN-3050	26	SG33BL-T-24V (DSUB)	80	MDB961WP-UAVCAN/DroneCAN-28V	136	HS-53	192
HLS12-CAN-5050	28	SG33BL-T-CAN-12V (Gland Cable)	82	MD65MG-CAN/UAV/DroneCAN	138	HS-81	194
HLS12-CAN-10050	30	SG33BL-T-CAN-12V (CIRCULAR)	84	MD70MH-CAN/UAVCAN/DroneCAN	140	HS-85MG	196
HLS12-CAN-30100	32	SG33BL-T-24V (Gland Cable)	86	MD85MG-CAN/UAVCAN/DroneCAN	142	HS-311	198
HLS12-CAN-50100	34	SG33BL-T-CAN-24V (CIRCULAR)	88	MD89MW-CAN/UAVCAN/DroneCAN	144	HS-322HD	200
HLS12-CAN-100100	36	SG50BL-CAN-24V (Circular)	90	MD145SW-CAN/UAVCAN/DroneCAN	146	HS-325HB	202
HLS12-CAN-30210	38	HSR-2645CRH	92	MD245MW-CAN/UAVCAN/DroneCAN	148	HS-645MG	204
HLS12-CAN-50210	40	HSB-9465SH	94	MD250MW-CAN/UAVCAN/DroneCAN	150	HS-646WP	206
HLS12-CAN-100210	42	HSB-9485SH	96	MD950TW-CAN/UAVCAN/DroneCAN	152	HS-1005SGT	208
HLS12-CAN-30380	44	HSB-9381TH	98	MD85MG	154	HS-1100WP	210
HLS12-CAN-50380	46	HSB-M9381TH	100	MD250MW	156	HS-5125MG	212
HLS12-CAN-100380	48	DB950SW	102	MD261SW	158	HS-5245MG	214
HLS12-RS485-3050	50	DB951WP	104	MD485HW	160	HS-5565MG	216
HLS12-RS485-5050	52	DB961WP	106	MD980TW	162	HS-7955TG	218

HS-M7990TH [220](#)

HSB-9485SH-270° [222](#)

HS-425BB [224](#)

HS-77BB [226](#)

HS-5685MH [228](#)

HS-5765MH [230](#)

Individual adaptation [233](#)

Programming devices [234](#)

SERVO OUTPUT ARMS

15T (Ø4,0) [236](#)

25T (Ø6,0) [237](#)

24T (Ø5,0) [237](#)

H25T (Ø6,0) [240](#)

15T (Ø8,0) [241](#)


Square 4 [242](#)

Square 5 [242](#)

Square 6.5 [243](#)

Square 10 [243](#)

Square 12 [243](#)



Since 2002, MULTIPLEX Modellsport GmbH & Co.KG, based in Bretten, Germany, is part of the South Korean HITEC Group.

The products of Hitec RCD Korea, Inc. are used worldwide and, due to their diversity, are suitable for a wide variety of applications. For example, they are used as servos in the UAV sector, as actuators for automation and handling tasks in industry, or as actuators for the active aerodynamics of a racecar.

We will be happy to send you detailed specifications and additional information on request.

Contact us under:

Phone: +49 (0) 7252 58093-20

Email: [saleteam@multiplex-cs.de](mailto:salesteam@multiplex-cs.de)



MULTIPLEX Modellsport
GmbH & Co.KG



Hitec RCD Korea, Inc.



Hitec Group USA, Inc.



Hitec-MULTIPLEX Japan, Inc.



Hitec RCD Philippines, Inc.

PRODUCT OVERVIEW

Servos and linear actuators

HLS-series linear actuators

SG-series servos

HSB/HSR-series servos

D/DB/MD/MDB-series servos

Other servos for related industrial applications

Servo accessories

a. Programming devices

b. Servo output arms



ANALOGUE ACTUATORS

Analogue actuators are generally low-priced to mid-priced items, and most of them are equipped with inexpensive components. The motor is always a D.C. brushed unit. Actuators offer no user-programmable options. Communication is always based on a PWM signal with a frequency of 50Hz. The motor PWM is the same as the control frequency, i.e. it is also 50Hz. This means that the possibility to control activity (motor on or motor off) only occurs every 20ms. Slow movements or small corrections result in long motor-off periods in relation to motor-on periods. The motor voltage is always the same as the power supply voltage.

Advantages:

- Reasonable price
- Pleasant running sound thanks to low motor frequency
- Low power consumption

Disadvantages:

- Low holding moment
- Slow response characteristics
- Low resolution due to low control frequency
- Wide deadband (20ms)
- Slow movements may not be smooth

DIGITAL ACTUATORS

Digital actuators generally fall in the high mid-range to high-price category. Very high-quality components may be used, such as Hall sensors for position sensing, as well as brushless D.C. motors. Communication is based on a PWM signal with frequencies up to 330Hz (according to actuator type) or other interfaces such as CAN, UAVCAN, RS-485 or TTL. The motor frequency is independent of the control system and is usually in the range 300 - 500Hz. This results in a very small possible deadband of up to 2ms. Digital actuators also offer wide-ranging programming and protective functions, as well as allowing two-way communication (feedback) depending on type.

Advantages:

- Fast response characteristics
- Fast corrective activity
- High holding power
- User-variable deadband
- Good accuracy
- Two-way communication
- Programmability
- Safety functions
- High resolution

Disadvantages:

- In most cases more expensive
- In some cases unpleasant running sound due to high motor frequency
- Higher power consumption



INTERFACES

PWM communication

The conventional method of controlling Hitec actuators, with many advantages for simple tasks. Hitec PWM actuators can be controlled using a pulse width of 900 to 2100µs. The usual control frequency is 50Hz (20ms), but frequencies up to 330Hz are possible with particular actuator types for special applications.

Actuators with PWM communication can easily be controlled at low cost, and they are adequate for many applications where feedback is not required.

The interface is in widespread use, and many controllers offer suitable presets and libraries.

Pin layout of Hitec PWM actuators*



RS485 and TTL communication

There are a number of applications in several fields of operation for which feedback of the actual servo position is required, or at least desirable. Certain Hitec actuators are also available with RS485 and TTL interfaces, which enable them to work with two-way communication (feedback).

Hitec RS485 and TTL actuators communicate with external devices using the half-duplex process. TTL actuators of this type feature just one signal wire in addition to the voltage and earth conductors, whereas RS485 actuators feature two signal wires.

Pin layout of Hitec TTL actuators*



Pin layout of Hitec RS485 actuators*



FEATURE OVERVIEW

Mid-point and end-point adjustment (EPA / Neutral Settings)

Provides programmable mid-point and end-point servo positions.

Direction of rotation

Clockwise (CW) = when viewed from above, the servo output rotates clockwise when the signal width is increased.

Counter-Clockwise (CCW) = when viewed from above, the servo output rotates counter-clockwise when the signal width is increased.

Deadband (DB width)

The smaller the deadband, the sooner any corrective activity takes place when an angular change occurs. If the deadband is too low for the application, the result will be increased wear. Increasing the deadband results in loss of precision.

Travel speed

The servo's transit speed: 100% equates to maximum possible travel speed.

ID-read / Node-ID

Assignment of an actuator ID in TTL and CAN networks.

Fail Safe

If the signal is lost, the servo rotates to a pre-selected position.

Fail Safe limp mode

The servo goes into sleep mode: the motor is disabled and the servo position is not maintained. The servo can be moved by hand.

Soft Start setting

When switched on, the servo runs to the nominal position at low speed in order to minimise stress on the gearbox and peripherals. At the 100% setting the servo runs to the nominal position with maximum transit speed when switched on.

Overload protection

Protection mechanism designed to avoid damage to the servo if it is overloaded or stalled. A setting of 20% corresponds to a reduction in maximum torque by 80%.

Smart sense

An intelligent regulatory circuit adjusts the control parameters while the servo is in use, in order to reduce oscillation. Oscillation can be provoked by fluctuating inertia levels in the various applications.

It is also possible to influence the regulatory circuit manually (sensitivity ratio settings). A high value may result in high-speed oscillation at the servo. A low value may generate severely damped response characteristics.



SERIES SUMMARY

HLS-series (Linear Actuators)

Electrical linear actuators generating straight-line travel movements, making them suitable as replacements for pneumatic and hydraulic cylinders in many applications.

SG-series (Industrial Servos)

The premium industrial servo line, consistently developed for requirements in the fields of automation, unmanned aviation and robotics. Basic equipment includes a powerful BLDC motor, a Hall sensor for zero-contact, zero-wear position sensing, and watertight construction. All SG-series servos also feature a Multi-Turn* and Continuous-Rotation** function.

HSB-series (Brushless Servos)

Mid-priced servo motors with powerful BLDC motors.

HSR-series (Servos with Multi-Turn)

Mid-priced servo motors with Multi-Turn* and in some cases Continuous-Rotation** function. Most are equipped with a BLDC motor.

D-series (Digital Servos)

Mid-priced digital servo motors with a coreless or brushed motor. Fitted with a high-quality potentiometer for position sensing.

MD-series (Digital Servos with Magnetic Encoder)

Mid-priced digital servo motors with a coreless or brushed motor. Fitted with a Hall sensor for position sensing.

DB-series (Brushless Servos)

Mid-priced digital servo motors with powerful BLDC motors. Fitted with a high-quality potentiometer for position sensing.

MDB-series (Brushless Servos with Magnetic Encoder)

Mid-priced digital servo motors with powerful BLDC motors. Fitted with a Hall sensor for position sensing.

MDR-series (Digital Servos with Magnetic Encoder and Multi-Turn)

Mid-priced digital servo motors with Multi-Turn* and in some cases Continuous-Rotation** function. Fitted with a coreless or brushed motor. Fitted with a Hall sensor for position sensing.

HS-series (Hitec Servo)

Low-priced analogue servo motors, fitted with a brushed motor and a potentiometer for position sensing.

HS-1XXX, HS-5XXX, HS-7XXX series (Hitec Servo)

Mid-priced digital servo motors fitted with a coreless or brushed motor and a potentiometer for position sensing.

*: Several rotations are possible for maximum angular travel.
**: The servo is capable of continuous rotation.

TWO-WAY COMMUNICATION (FEEDBACK)

Absolute position

The control system no longer has to rely on an actuator actually taking up the desired position; instead its current position can be read off with a resolution of 4096 steps.

Torque

Torque is a particularly important feature, as it allows the user to make assessments of the actual loads when the actuator is in use, as well as the condition of the components. Stiff mechanical systems can be detected and corrected in good time before they result in actuator overload. The torque value is derived from the motor PWM, and is therefore not an actual measurement, but it is adequately precise for the majority of applications.

Speed

How fast is the actuator when actually in use by the application? The actuator itself supplies the answer, thereby permitting important inferences to be drawn for many a control task.

Power supply voltage

The actuator constantly provides information on the momentary power supply voltage. The development or maintenance team can use this to detect potential weak points in the cable loom, for example: enabling high-resistance connectors to be replaced in good time.

Current drain

Current is the most important feedback element in preventing potential damage. Rising current over a given period of operation under a constant load is a reliable indication of an imminent fault. This may relate to the motor, the gearbox or the mechanical system being moved. Monitoring current drain opens up new possibilities in programming: effective system life can be extended by targeted optimisation of the internal control system (PID) and other parameters such as Soft Start (ramp) or deadband.

Micro-controller temperature

The temperature of the micro-controller is more than just a useful piece of information. Environmental conditions which include wide thermal variation can be very demanding on an actuator. Monitoring temperature in this way allows the development team to learn the thermal limits of the product, and to introduce appropriate measures to prevent premature failure.

Motor temperature

Are you asking too much of the actuator you are using? The motor temperature provides reliable information on whether an actuator is being operated close to its limit. This feedback is very important, especially if thermal conditions are widely variable.

Cycle counter

How many cycles does the actuator complete during use? How many parts were positioned? When must the actuator be replaced because the maximum cycle count has been reached? Some of our actuators supply this feedback in a convenient manner as part of the protocol.

MOTORTYPES OVERVIEW

Brushed Motor

Brushed DC motors are characterized primarily by their low price, but also by their high overload capacity (good heat dissipation). These motors are mainly used in analog servos. They are a first choice for applications with lower performance requirements or a relatively low number of cycles (e.g. locking mechanisms). The disadvantages are, in addition to the wear and tear of the sliders, an increased cogging torque and lower efficiency. The motor ramp-up time (acceleration) is between 22 and 40ms, depending on the type.

Coreless Motor

These extremely efficient motors (no cyclic magnetization losses) impress with very fast motor ramp-up times (acceleration) of just 7 to 11ms and high power delivery. Due to their design, (iron-)coreless motors have no cogging torque, which is reflected in smooth engine running. The wear is low and relates only to the conductor, which is used for commutation, and the bearings. A disadvantage is the low overload capacity of the coreless design, due to poor heat dissipation. Coreless motors therefore recommended for use in more demanding applications, where there are also occasional rest phases between cycles to allow cooling, or for control and regulation tasks in the low load range.

Brushless Motor

Powerful BLDC motors combine many advantages of modern drive technology and are almost wear-free (no sliders). In addition to high efficiency and smooth running, sensor-controlled brushless motors also offer a fast motor ramp-up time (acceleration) of just 11 to 14 ms and high torque right from a standing start. In contrast to coreless motors, good heat dissipation is provided via the laminated core, which minimizes thermal problems during continuous operation. These motors are highly recommended for demanding applications with frequent corrective measures. Most high-load actuators are therefore equipped with BLDC motors.



DMSZ
Z E R T I F I K A T

Die
Deutsche Managementsystem Zertifizierungsgesellschaft mbH
bescheinigt hiermit, dass das Unternehmen

Multiplex Modellsport GmbH & Co. KG
Westliche Gewerbestr.1
75015 Bretten

MULTIPLEX
COMMERCIAL SOLUTIONS

für den Geltungsbereich
Produktion, Entwicklung und Handel von Flugmodellen, Fernsteuersystemen,
Aktuatoren sowie Lade-, Antriebs- und Regeltechnologie im
Modellsport und Industriebereich.

ein
Qualitätsmanagementsystem
eingeführt hat und anwendet.

Durch ein Audit, dokumentiert in einem Bericht, wurde der Nachweis erbracht,
dass dieses Qualitätsmanagementsystem die Forderungen der folgenden Norm erfüllt:

DIN EN ISO 9001:2015
Ausgabe November 2015

Dieses Zertifikat ist gültig vom 05.12.2022 bis 04.12.2025
Zertifikat-Registrier-Nr.: QM 22118-Z02443
Griesheim, den 05.12.2022

D. Kaiser
(Geschäftsführer)

Hans-W. Lortz
(Leiter Zertifizierungsstelle)

IAF
INTERNATIONAL ASSOCIATION FOR ACCREDITED CERTIFICATION BODIES

DAkkS
Deutsche Akkreditierungsstelle
D-ZM-16033-01-00




HLS LINEAR ACTUATORS



HLS12-3050, -30100, -30210, -30380


#1-02453, #1-03232, #1-02454, #1-02455

GENERAL SPECIFICATION

HLS12-30XXX										
Control System	PWM 1000usec ~ 2000usec									
Position Sensor Type	-									
Operating Voltage Range	4.0 ~ 8.4V									
Motor Type	Cored Metal Brush									
Amplifier / MCU	32bits programmable Digital									
Lead Screw	Lead 5mm									
Stroke Option	30mm									
Repeatability	±0.2mm									
Gear Ratio	50:1	100:1	210:1	380:1						
Voltage	At 7.4V			At 7.4V			At 7.4V		At 7.4V	
Speed at no Load	30.9mm/s			16.1mm/s			7.5mm/s		4.1mm/s	
Running Current at no Load	130mA			130mA			130mA		130mA	
Load Spec	Load	Speed	Current	Load	Speed	Current	Load	Speed	Current	Load
Maximum Efficiency Point	1.2kg (11.8N)	23.5mm/s	250mA	2.1kg (20.6N)	12.7mm/s	250mA	4.4kg (43.2N)	5.6mm/s	250mA	8.0kg (78.5N)
Peak Power Point	2.1kg (20.6N)	17.3mm/s	370mA	3.8kg (37.3N)	8.6mm/s	370mA	7.7kg (75.5N)	4.0mm/s	370mA	12.4kg (121.6N)
Max Force (Lifted)	2.7kg (26.5N)	8.2mm/s	490mA	5.2kg (51.0N)	4.0mm/s	490mA	9.9kg (97.1N)	2.8mm/s	490mA	14.8kg (145.2N)
Stall Torque	3.1kg (30.4N)			6.2kg (60.8N)			12.4kg (121.6N)			22.2kg (217.8N)
Stall Current	620mA									
Max Static Force	25.2kg (247N) (above)									
Max Side Load (Extended)	4.1kg (40N)									
Operating Temperature Range	-10°C ~ +50°C (14°F ~ +122°F)									
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)									
Vibrations at no Load	-									
Connector Wire Length	160mm									
Connector Wire Gauge	24AWG									
Connector Wire Strand Count	40/0.08									
External Dimensions	82.0 x 15.0 x 18.0mm									
Weight	34.0g									
Ball Bearing	Flange Bearing									
Case Material	Engineering Plastic & Aluminum Pipe									
Gear Material	4 Metal Gears									
IP-Rating	IP4X									
Revision	Rev. 1.1 / 02.01.2024									
Changelog	-									

HLS12-5050, -50100, -50210, -50380


#1-02456, #03233, #1-02457, #1-02458

GENERAL SPECIFICATION

HLS12-50XXX										
Control System	PWM 1000usec ~ 2000usec									
Position Sensor Type	-									
Operating Voltage Range	4.0 ~ 8.4V									
Motor Type	Cored Metal Brush									
Amplifier / MCU	32bits programmable Digital									
Lead Screw	Lead 5mm									
Stroke Option	50mm									
Repeatability	±0.3mm									
Gear Ratio	50:1	100:1	210:1	380:1						
Voltage	At 7.4V				At 7.4V			At 7.4V		At 7.4V
Speed at no Load	30.9mm/s				16.1mm/s			7.5mm/s		4.1mm/s
Running Current at no Load	130mA				130mA			130mA		130mA
Load Spec	Load	Speed	Current	Load	Speed	Current	Load	Speed	Current	Load
Maximum Efficiency Point	1.2kg (11.8N)	23.5mm/s	250mA	2.1kg (20.6N)	12.7mm/s	250mA	4.4kg (43.2N)	5.6mm/s	250mA	8.0kg (78.5N)
Peak Power Point	2.1kg (20.6N)	17.3mm/s	370mA	3.8kg (37.3N)	8.6mm/s	370mA	7.7kg (75.5N)	4.0mm/s	370mA	12.4kg (121.6N)
Max Force (Lifted)	2.7kg (26.5N)	8.2mm/s	490mA	5.2kg (51.0N)	4.0mm/s	490mA	9.9kg (97.1N)	2.8mm/s	490mA	14.8kg (145.2N)
Stall Torque	3.1kg (30.4N)			6.2kg (60.8N)			12.4kg (121.6N)			22.2kg (217.8N)
Stall Current	620mA									
Max Static Force	25.2kg (247N) (above)									
Max Side Load (Extended)	3.1kg (30N)									
Operating Temperature Range	-10°C ~ +50°C (14°F ~ +122°F)									
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)									
Vibrations at no Load	-									
Connector Wire Length	160mm									
Connector Wire Gauge	24AWG									
Connector Wire Strand Count	40/0.08									
External Dimensions	102.0 x 15.0 x 18.0mm									
Weight	40.0g									
Ball Bearing	Flange Bearing									
Case Material	Engineering Plastic & Aluminum Pipe									
Gear Material	4 Metal Gears									
IP-Rating	IP4X									
Revision	Rev. 1.1 / 02.01.2024									
Changelog	-									

HLS12-10050, -100100, -100210, -100380


#1-02496, #1-03234, #1-02460, #1-02461

GENERAL SPECIFICATION

HLS12-100XX										
Control System	PWM 1000usec ~ 2000usec									
Position Sensor Type	-									
Operating Voltage Range	4.0 ~ 8.4V									
Motor Type	Cored Metal Brush									
Amplifier / MCU	32bits programmable Digital									
Lead Screw	Lead 5mm									
Stroke Option	100mm									
Repeatability	±0.5mm									
Gear Ratio	50:1			100:1			210:1			380:1
Voltage	At 7.4V			At 7.4V			At 7.4V			At 7.4V
Speed at no Load	30.9mm/s			16.1mm/s			7.5mm/s			4.1mm/s
Running Current at no Load	130mA			130mA			130mA			130mA
Load Spec	Load	Speed	Current	Load	Speed	Current	Load	Speed	Current	Load
Maximum Efficiency Point	1.2kg (11.8N)	23.5mm/s	250mA	2.1kg (20.6N)	12.7mm/s	250mA	4.4kg (43.2N)	5.6mm/s	250mA	8.0kg (78.5N)
Peak Power Point	2.1kg (20.6N)	17.3mm/s	370mA	3.8kg (37.3N)	8.6mm/s	370mA	7.7kg (75.5N)	4.0mm/s	370mA	12.4kg (121.6N)
Max Force (Lifted)	2.7kg (26.5N)	8.2mm/s	490mA	5.2kg (51.0N)	4.0mm/s	490mA	9.9kg (97.1N)	2.8mm/s	490mA	14.8kg (145.2N)
Stall Torque	3.1kg (30.4N)			6.2kg (60.8N)			12.4kg (121.6N)			22.2kg (217.8N)
Stall Current	620mA									
Max Static Force	25.2kg (247N) (above)									
Max Side Load (Extended)	1.5kg (15N)									
Operating Temperature Range	-10°C ~ +50°C (14°F ~ +122°F)									
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)									
Vibrations at no Load	-									
Connector Wire Length	160mm									
Connector Wire Gauge	24AWG									
Connector Wire Strand Count	40/0.08									
External Dimensions	152.0 x 15.0 x 18.0mm									
Weight	56.0g									
Ball Bearing	Flange Bearing									
Case Material	Engineering Plastic & Aluminum Pipe									
Gear Material	4 Metal Gears									
IP-Rating	IP4X									
Revision	Rev. 1.1 / 02.01.2024									
Changelog	-									

HLS12-CAN-3050


1-03288

**GENERAL SPECIFICATION**

HLS12-CAN-3050			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	50:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	20.0mm/s	25.0mm/s	30.9mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	2.0kgf (19.61N)	2.5kgf (24.52N)	3.1kgf (30.40N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	0.8kgf (7.85N)	1.0kgf (9.81N)	1.2kgf (11.77N)
Maximum Efficiency Point Speed	15.2mm/s	19.0mm/s	23.5mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Peak Power Point Speed	11.2mm/s	14.0mm/s	17.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	1.8kgf (17.65N)	2.2kgf (21.57N)	2.7kgf (26.48N)
Max Force (Lifted) Speed	5.3mm/s	6.7mm/s	8.2mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-5050


1-03289

GENERAL SPECIFICATION

HLS12-CAN-5050			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	50:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	20.0mm/s	25.0mm/s	30.9mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	2.0kgf (19.61N)	2.5kgf (24.52N)	3.1kgf (30.40N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	0.8kgf (7.85N)	1.0kgf (9.81N)	1.2kgf (11.77N)
Maximum Efficiency Point Speed	15.2mm/s	19.0mm/s	23.5mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Peak Power Point Speed	11.2mm/s	14.0mm/s	17.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	1.8kgf (17.65N)	2.2kgf (21.57N)	2.7kgf (26.48N)
Max Force (Lifted) Speed	5.3mm/s	6.7mm/s	8.2mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-10050


1-03290

**GENERAL SPECIFICATION**

HLS12-CAN-10050			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	50:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	20.0mm/s	25.0mm/s	30.9mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	2.0kgf (19.61N)	2.5kgf (24.52N)	3.1kgf (30.40N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	0.8kgf (7.85N)	1.0kgf (9.81N)	1.2kgf (11.77N)
Maximum Efficiency Point Speed	15.2mm/s	19.0mm/s	23.5mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Peak Power Point Speed	11.2mm/s	14.0mm/s	17.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	1.8kgf (17.65N)	2.2kgf (21.57N)	2.7kgf (26.48N)
Max Force (Lifted) Speed	5.3mm/s	6.7mm/s	8.2mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-30100


1-03291

GENERAL SPECIFICATION

HLS12-CAN-30100			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	100:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	10.4mm/s	13.0mm/s	16.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	4.0kgf (39.23N)	5.0kgf (49.03N)	6.2kgf (60.80N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Maximum Efficiency Point Speed	8.2mm/s	10.3mm/s	12.7mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	2.5kgf (24.52N)	3.1kgf (30.40N)	3.8kgf (37.27N)
Peak Power Point Speed	5.6mm/s	7.0mm/s	8.6mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	3.2kgf (31.38N)	4.2kgf (41.19N)	5.2kgf (50.99N)
Max Force (Lifted) Speed	2.6mm/s	3.2mm/s	4.0mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-50100


1-03292

GENERAL SPECIFICATION

HLS12-CAN-50100			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	100:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	10.4mm/s	13.0mm/s	16.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	4.0kgf (39.23N)	5.0kgf (49.03N)	6.2kgf (60.80N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Maximum Efficiency Point Speed	8.2mm/s	10.3mm/s	12.7mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	2.5kgf (24.52N)	3.1kgf (30.40N)	3.8kgf (37.27N)
Peak Power Point Speed	5.6mm/s	7.0mm/s	8.6mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	3.2kgf (31.38N)	4.2kgf (41.19N)	5.2kgf (50.99N)
Max Force (Lifted) Speed	2.6mm/s	3.2mm/s	4.0mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-100100


1-03293

**GENERAL SPECIFICATION**

HLS12-CAN-100100			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	100:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	10.4mm/s	13.0mm/s	16.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	4.0kgf (39.23N)	5.0kgf (49.03N)	6.2kgf (60.80N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Maximum Efficiency Point Speed	8.2mm/s	10.3mm/s	12.7mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	2.5kgf (24.52N)	3.1kgf (30.40N)	3.8kgf (37.27N)
Peak Power Point Speed	5.6mm/s	7.0mm/s	8.6mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	3.2kgf (31.38N)	4.2kgf (41.19N)	5.2kgf (50.99N)
Max Force (Lifted) Speed	2.6mm/s	3.2mm/s	4.0mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-30210


1-03294

GENERAL SPECIFICATION

HLS12-CAN-30210			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	210:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	4.9mm/s	6.1mm/s	7.5mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	2.9kgf (28.44N)	3.6kgf (35.30N)	4.4kgf (43.15N)
Maximum Efficiency Point Speed	3.6mm/s	4.5mm/s	5.6mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	5.6kgf (54.92N)	7.0kgf (68.65N)	8.6kgf (84.34N)
Peak Power Point Speed	2.6mm/s	3.2mm/s	4.0mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	6.4kgf (62.76N)	8.0kgf (78.45N)	9.9kgf (97.09N)
Max Force (Lifted) Speed	1.8mm/s	2.3mm/s	2.8mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-50210


1-03295

GENERAL SPECIFICATION

HLS12-CAN-50210			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	210:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	4.9mm/s	6.1mm/s	7.5mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	2.9kgf (28.44N)	3.6kgf (35.30N)	4.4kgf (43.15N)
Maximum Efficiency Point Speed	3.6mm/s	4.5mm/s	5.6mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	5.6kgf (54.92N)	7.0kgf (68.65N)	8.6kgf (84.34N)
Peak Power Point Speed	2.6mm/s	3.2mm/s	4.0mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	6.4kgf (62.76N)	8.0kgf (78.45N)	9.9kgf (97.09N)
Max Force (Lifted) Speed	1.8mm/s	2.3mm/s	2.8mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-100210


1-03296

GENERAL SPECIFICATION

HLS12-CAN-100210			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	210:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	4.9mm/s	6.1mm/s	7.5mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	2.9kgf (28.44N)	3.6kgf (35.30N)	4.4kgf (43.15N)
Maximum Efficiency Point Speed	3.6mm/s	4.5mm/s	5.6mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	5.6kgf (54.92N)	7.0kgf (68.65N)	8.6kgf (84.34N)
Peak Power Point Speed	2.6mm/s	3.2mm/s	4.0mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	6.4kgf (62.76N)	8.0kgf (78.45N)	9.9kgf (97.09N)
Max Force (Lifted) Speed	1.8mm/s	2.3mm/s	2.8mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-30380


1-03297

GENERAL SPECIFICATION

HLS12-CAN-30380			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	380:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	2.6mm/s	3.3mm/s	4.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	14.4kgf (141.22N)	18.0kgf (176.52N)	22.2kgf (217.71N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	5.2kgf (50.99N)	6.5kgf (63.74N)	8.0kgf (78.45N)
Maximum Efficiency Point Speed	2.0mm/s	2.5mm/s	3.1mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Peak Power Point Speed	1.5mm/s	1.9mm/s	2.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	9.6kgf (94.14N)	12.0kgf (117.68N)	14.8kgf (145.14N)
Max Force (Lifted) Speed	1.0mm/s	1.2mm/s	1.5mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-50380


1-03298

GENERAL SPECIFICATION

HLS12-CAN-50380			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	380:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	2.6mm/s	3.3mm/s	4.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	14.4kgf (141.22N)	18.0kgf (176.52N)	22.2kgf (217.71N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	5.2kgf (50.99N)	6.5kgf (63.74N)	8.0kgf (78.45N)
Maximum Efficiency Point Speed	2.0mm/s	2.5mm/s	3.1mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Peak Power Point Speed	1.5mm/s	1.9mm/s	2.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	9.6kgf (94.14N)	12.0kgf (117.68N)	14.8kgf (145.14N)
Max Force (Lifted) Speed	1.0mm/s	1.2mm/s	1.5mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-CAN-100380


1-03299

GENERAL SPECIFICATION

HLS12-CAN-100380			
Control System	CAN2.0A, B		
Position Sensor Type	-		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	380:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	2.6mm/s	3.3mm/s	4.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	14.4kgf (141.22N)	18.0kgf (176.52N)	22.2kgf (217.71N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	5.2kgf (50.99N)	6.5kgf (63.74N)	8.0kgf (78.45N)
Maximum Efficiency Point Speed	2.0mm/s	2.5mm/s	3.1mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Peak Power Point Speed	1.5mm/s	1.9mm/s	2.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	9.6kgf (94.14N)	12.0kgf (117.68N)	14.8kgf (145.14N)
Max Force (Lifted) Speed	1.0mm/s	1.2mm/s	1.5mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-3050


1-03301

GENERAL SPECIFICATION

HLS12-RS485-3050			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	50:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	20.0mm/s	25.0mm/s	30.9mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	2.0kgf (19.61N)	2.5kgf (24.52N)	3.1kgf (30.40N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	0.8kgf (7.85N)	1.0kgf (9.81N)	1.2kgf (11.77N)
Maximum Efficiency Point Speed	15.2mm/s	19.0mm/s	23.5mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Peak Power Point Speed	11.2mm/s	14.0mm/s	17.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	1.8kgf (17.65N)	2.2kgf (21.57N)	2.7kgf (26.48N)
Max Force (Lifted) Speed	5.3mm/s	6.7mm/s	8.2mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-5050


1-03302

GENERAL SPECIFICATION

HLS12-RS485-5050			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	50:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	20.0mm/s	25.0mm/s	30.9mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	2.0kgf (19.61N)	2.5kgf (24.52N)	3.1kgf (30.40N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	0.8kgf (7.85N)	1.0kgf (9.81N)	1.2kgf (11.77N)
Maximum Efficiency Point Speed	15.2mm/s	19.0mm/s	23.5mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Peak Power Point Speed	11.2mm/s	14.0mm/s	17.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	1.8kgf (17.65N)	2.2kgf (21.57N)	2.7kgf (26.48N)
Max Force (Lifted) Speed	5.3mm/s	6.7mm/s	8.2mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-10050


1-03303

**GENERAL SPECIFICATION**

HLS12-RS485-10050			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	50:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	20.0mm/s	25.0mm/s	30.9mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	2.0kgf (19.61N)	2.5kgf (24.52N)	3.1kgf (30.40N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	0.8kgf (7.85N)	1.0kgf (9.81N)	1.2kgf (11.77N)
Maximum Efficiency Point Speed	15.2mm/s	19.0mm/s	23.5mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Peak Power Point Speed	11.2mm/s	14.0mm/s	17.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	1.8kgf (17.65N)	2.2kgf (21.57N)	2.7kgf (26.48N)
Max Force (Lifted) Speed	5.3mm/s	6.7mm/s	8.2mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-30100


1-03304

**GENERAL SPECIFICATION**

HLS12-RS485-30100			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	100:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	10.4mm/s	13.0mm/s	16.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	4.0kgf (39.23N)	5.0kgf (49.03N)	6.2kgf (60.80N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Maximum Efficiency Point Speed	8.2mm/s	10.3mm/s	12.7mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	2.5kgf (24.52N)	3.1kgf (30.40N)	3.8kgf (37.27N)
Peak Power Point Speed	5.6mm/s	7.0mm/s	8.6mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	3.2kgf (31.38N)	4.2kgf (41.19N)	5.2kgf (50.99N)
Max Force (Lifted) Speed	2.6mm/s	3.2mm/s	4.0mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-50100


1-03305

**GENERAL SPECIFICATION**

HLS12-RS485-50100			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	100:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	10.4mm/s	13.0mm/s	16.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	4.0kgf (39.23N)	5.0kgf (49.03N)	6.2kgf (60.80N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Maximum Efficiency Point Speed	8.2mm/s	10.3mm/s	12.7mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	2.5kgf (24.52N)	3.1kgf (30.40N)	3.8kgf (37.27N)
Peak Power Point Speed	5.6mm/s	7.0mm/s	8.6mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	3.2kgf (31.38N)	4.2kgf (41.19N)	5.2kgf (50.99N)
Max Force (Lifted) Speed	2.6mm/s	3.2mm/s	4.0mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-100100


1-03306

**GENERAL SPECIFICATION**

HLS12-RS485-100100			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	100:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	10.4mm/s	13.0mm/s	16.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	4.0kgf (39.23N)	5.0kgf (49.03N)	6.2kgf (60.80N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	1.4kgf (13.73N)	1.7kgf (16.67N)	2.1kgf (20.59N)
Maximum Efficiency Point Speed	8.2mm/s	10.3mm/s	12.7mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	2.5kgf (24.52N)	3.1kgf (30.40N)	3.8kgf (37.27N)
Peak Power Point Speed	5.6mm/s	7.0mm/s	8.6mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	3.2kgf (31.38N)	4.2kgf (41.19N)	5.2kgf (50.99N)
Max Force (Lifted) Speed	2.6mm/s	3.2mm/s	4.0mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-30210


1-03307

**GENERAL SPECIFICATION**

HLS12-RS485-30210			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	210:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	4.9mm/s	6.1mm/s	7.5mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	2.9kgf (28.44N)	3.6kgf (35.30N)	4.4kgf (43.15N)
Maximum Efficiency Point Speed	3.6mm/s	4.5mm/s	5.6mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	5.6kgf (54.92N)	7.0kgf (68.65N)	8.6kgf (84.34N)
Peak Power Point Speed	2.6mm/s	3.2mm/s	4.0mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	6.4kgf (62.76N)	8.0kgf (78.45N)	9.9kgf (97.09N)
Max Force (Lifted) Speed	1.8mm/s	2.3mm/s	2.8mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-50210


1-03308

**GENERAL SPECIFICATION**

HLS12-RS485-50210			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	210:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	4.9mm/s	6.1mm/s	7.5mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	2.9kgf (28.44N)	3.6kgf (35.30N)	4.4kgf (43.15N)
Maximum Efficiency Point Speed	3.6mm/s	4.5mm/s	5.6mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	5.6kgf (54.92N)	7.0kgf (68.65N)	8.6kgf (84.34N)
Peak Power Point Speed	2.6mm/s	3.2mm/s	4.0mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	6.4kgf (62.76N)	8.0kgf (78.45N)	9.9kgf (97.09N)
Max Force (Lifted) Speed	1.8mm/s	2.3mm/s	2.8mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-100210


1-03309

**GENERAL SPECIFICATION**

HLS12-RS485-100210			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	210:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	4.9mm/s	6.1mm/s	7.5mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	2.9kgf (28.44N)	3.6kgf (35.30N)	4.4kgf (43.15N)
Maximum Efficiency Point Speed	3.6mm/s	4.5mm/s	5.6mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	5.6kgf (54.92N)	7.0kgf (68.65N)	8.6kgf (84.34N)
Peak Power Point Speed	2.6mm/s	3.2mm/s	4.0mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	6.4kgf (62.76N)	8.0kgf (78.45N)	9.9kgf (97.09N)
Max Force (Lifted) Speed	1.8mm/s	2.3mm/s	2.8mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-30380


1-03310

GENERAL SPECIFICATION

HLS12-RS485-30380			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	30mm		
Repeatability	±0.2mm		
Gear Ratio	380:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	2.6mm/s	3.3mm/s	4.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	14.4kgf (141.22N)	18.0kgf (176.52N)	22.2kgf (217.71N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	5.2kgf (50.99N)	6.5kgf (63.74N)	8.0kgf (78.45N)
Maximum Efficiency Point Speed	2.0mm/s	2.5mm/s	3.1mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Peak Power Point Speed	1.5mm/s	1.9mm/s	2.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	9.6kgf (94.14N)	12.0kgf (117.68N)	14.8kgf (145.14N)
Max Force (Lifted) Speed	1.0mm/s	1.2mm/s	1.5mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	4.08kgf (40N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	82.0mm x 15.0mm x 18.0mm (3.228inch x 0.591inch x 0.709inch)		
Weight	34g (1.199oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-50380

1-03311


GENERAL SPECIFICATION

HLS12-RS485-50380			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	50mm		
Repeatability	±0.3mm		
Gear Ratio	380:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	2.6mm/s	3.3mm/s	4.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	14.4kgf (141.22N)	18.0kgf (176.52N)	22.2kgf (217.71N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	5.2kgf (50.99N)	6.5kgf (63.74N)	8.0kgf (78.45N)
Maximum Efficiency Point Speed	2.0mm/s	2.5mm/s	3.1mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Peak Power Point Speed	1.5mm/s	1.9mm/s	2.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	9.6kgf (94.14N)	12.0kgf (117.68N)	14.8kgf (145.14N)
Max Force (Lifted) Speed	1.0mm/s	1.2mm/s	1.5mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	3.06kgf (30N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	102.0mm x 15.0mm x 18.0mm (4.016inch x 0.591inch x 0.709inch)		
Weight	40g (1.411oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

HLS12-RS485-100380

1-03312



GENERAL SPECIFICATION



HLS12-RS485-100380			
Control System	RS485		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.0 ~ 8.4V		
Servo Amplifier Type	32bit programmable Digital		
Stroke Option	100mm		
Repeatability	±0.5mm		
Gear Ratio	380:1		
Voltage	4.8V	6.0V	7.4V
Speed at no Load	2.6mm/s	3.3mm/s	4.1mm/s
Running Current at no Load	80mA	100mA	130mA
Stall Force	14.4kgf (141.22N)	18.0kgf (176.52N)	22.2kgf (217.71N)
Stall Current	400mA	500mA	620mA
Maximum Efficiency Point Load	5.2kgf (50.99N)	6.5kgf (63.74N)	8.0kgf (78.45N)
Maximum Efficiency Point Speed	2.0mm/s	2.5mm/s	3.1mm/s
Maximum Efficiency Point Current	160mA	200mA	250mA
Peak Power Point Load	8.0kgf (78.45N)	10.0kgf (98.07N)	12.4kgf (121.60N)
Peak Power Point Speed	1.5mm/s	1.9mm/s	2.3mm/s
Peak Power Point Current	240mA	300mA	370mA
Max Force (Lifted) Load	9.6kgf (94.14N)	12.0kgf (117.68N)	14.8kgf (145.14N)
Max Force (Lifted) Speed	1.0mm/s	1.2mm/s	1.5mm/s
Max Force (Lifted) Current	320mA	400mA	490mA
Max Side Load (Extended)	1.53kgf (15N)		
Operating Temperature Range	-10°C ~ +50°C		
Storage Temperature Range	-30°C ~ +80°C		
Connector Wire Length	160mm(6.294inch)		
Connector Wire Gauge	24AWG		
Outline Dimensions	152.0mm x 15.0mm x 18.0mm (5.984inch x 0.591inch x 0.709inch)		
Weight	56g (1.975oz)		
Bearing Type	Flange bearing		
Case Material	Engineering Plastic & Aluminum Pipe		
Gear Material	4 Metal Gears		
IP-Rating	IP4X		

SG15BL-CAN (M5 CIRCULAR)



#1-03282

GENERAL SPECIFICATION

SG15BL-CAN (M5 Circular)			
Control System	CAN 2.0A,B / DroneCAN (UAVCAN v0)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	9.0V ~ 15.0V		
Voltage	At 12.0V		
No Load Speed	487.8 °/sec	0.123 sec/60°	81.3 RPM
Rated Torque (At 20% Load)	0.216 N·m (2.2 kgf·cm)		
Peak Torque	1.08 N·m (11.0 kgf·cm)		
Idle Current (At Stopped)	35mA		
Running Current (At No Load)	200mA		
Peak Current	2,000mA		
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable)		
Multi-Turn	Turn Mode : ±32760 turns (DroneCAN: n/a)		
Servo Amplifier Type	32bit Programmable Digital		
Dimensions	31.0 x 15.0 x 50.0mm (±0.2mm) / (1.220 x 0.590 x 1.969 inch)		
Weight	62.5g (±10%)		
Housing	Rugged Aluminum Alloy With Hardcoat Anodizing		
Gear Reduction	5 Hardened Steel Gears		
Bearing	8 Ball Bearing & 3 Needle Bearing & 1 Thrust Bearing		
Horn Gear Spline	Square 5.0 x 5.0		
Gear Train Backlash	< 0.5°		
Operation Temperature	-30°C (-22°F) bis +70°C (+158°F)		
MTTF	>1,000h		
Radial Load On Output Shaft	< 129.55N (13.21kgf)		
Push Load On Output Shaft	< 1,025N (104.52kgf)		
Connector Type	Circular		
Connector	M5 4 Pins Female Panel Mount (M5*0.75 Front Fastened DIP)		
IP-Rating	IP68		

SG20BL-CAN-12V (M8 CIRCULAR)



#1-03169

**GENERAL SPECIFICATION**

SG20BL-CAN-12V (M8 Circular)		
Control System	CAN 2.0A,B / DroneCAN (UAVCAN v0)	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	BLDC Motor	
Operating Voltage Range	9.0V ~ 15.0V	
Voltage	At 12.0V	
No Load Speed	463.0 °/sec	0.13 sec/60° 77.17 RPM
Rated Torque (At 20% Load)	1.27 N·m (13.0 kgf·cm)	
Peak Torque	6.37 N·m (65.0 kgf·cm)	
Idle Current (At Stopped)	30mA	
Running Current (At No Load)	500mA	
Peak Current	4,000mA	
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable)	
Multi-Turn	Turn Mode : ±32760 turns (DroneCAN: n/a)	
Servo Amplifier Type	32bit Programmable Digital	
Dimensions	45.0 x 20.0 x 75.0mm (±0.2mm) / (1.772 x 0.787 x 2.953 inch)	
Weight	Non-Clutch Type : 170g (±10%)	
Housing	Rugged Aluminum Alloy With Hardcoat Anodizing	
Gear Reduction	5 Hardened Steel Gears	
Bearing	3 Ball Bearing & 6 Needle Bearing & 1 Thrust Bearing	
Horn Gear Spline	Square 6.5 x 6.5	
Gear Train Backlash	< 0.5°	
Operation Temperature	-30°C (-22°F) bis +70°C (+158°F)	
MTTF	>1,000h	
Radial Load On Output Shaft	<764.92N (78.0kgf)	
Push Load On Output Shaft	<1,570N (160kgf)	
Connector Type	Circular	
Connector	M8 B-coding 5 Pins Female Panel Mount With Wires(Front fastened)	
IP-Rating	IP68	

SG33BL-T-12V (DSUB)

#1-00932


**PERFORMANCE CHART****GENERAL SPECIFICATION**

SG33BL-T-12V (DSUB)		
Control System	PWM / RS485 / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	D-Sub 9	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	BLDC	
Amplifier / MCU	32bit programmable Digital	
Operating Voltage Range	9.0V ~ 15.0V	
Operating Voltage	At 12.0V	
Operating Speed at no Load	324°/s (54RPM)	
Stall Torque	147.0kgcm (1442.1Ncm)	
Rest Current	30mA	
Running Current at no Load	500mA	
Stall Current	10000mA	
Deadband Width	2µs	
Operating Travel	Default	±60°
	Programmable	±160°
	Multi Turn	±2880° (Max ±8 Turns)
	Continuous Rotation	n/a
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)	
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)	
Vibrations at no Load	MIL-STD-810G 514.6C-VII / EN60068-2-6	
Connector Wire Length	-	
Connector Wire Gauge	-	
Connector Wire Strand Count	-	
External Dimensions	64.0 x 33.0 x 95.0mm	
Weight*	480.0g	
Ball Bearing	6 Ball Bearings & 2 Needle Bearings	
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing	
Gear Material	4 Hardened Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	Square 6.5 x 6.5	
Accessories	Mounting Hardware, Servo Horn (I-MOS)	
IP-Rating	IP68	
MTTF	>1000h	
Revision & Stand	Rev. 1.2 / 01.02.2024	
Changelog	-	


*of the servo only w/o horns and accessories

SG33BL-T-24V (DSUB)

#1-02462



PERFORMANCE CHART




GENERAL SPECIFICATION

SG33BL-T-24V (DSUB)		
Control System	PWM / RS485 / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	D-Sub 9	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	BLDC	
Amplifier / MCU	32bit programmable Digital	
Operating Voltage Range	22.0V ~ 26.0V	
Operating Voltage	At 24.0V	
Operating Speed at no Load	324°/s (54RPM)	
Stall Torque	147.00kgcm (1442.1Ncm)	
Idle Current	20mA	
No Load Running Current	230mA	
Stall Current	6400mA	
Deadband Width	2µs	
Operating Travel	Default	±60°
	Programmable	±160°
	Multi Turn	±2880° (Max ±8 Turns)
	Continuous Rotation	n/a
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)	
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)	
Vibrations at no Load	MIL-STD-810G 514.6C-VII / EN60068-2-6	
Connector Wire Length	-	
Connector Wire Gauge	-	
Connector Wire Strand Count	-	
External Dimensions	64.0 x 33.0 x 95.0mm	
Weight*	480.0g	
Ball Bearing	6 Ball Bearings & 2 Needle Bearings	
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing	
Gear Material	4 Hardened Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	Square 6.5 x 6.5	
Accessories	Mounting Hardware, Servo Horn (I-MOS)	
IP-Rating	IP68	
MTTF	>1000h	
Revision & Stand	Rev. 1.2 / 01.02.2024	
Changelog	-	


*of the servo only w/o horns and accessories

SG33BL-T-CAN-12V(GLANDCABLE)

#1-02345



1:2


PERFORMANCE CHART**GENERAL SPECIFICATION**

SG33BL-T-CAN-12V (Gland Cable)			
Control System	CAN 2.0A,B / DroneCAN (UAVCAN v0)	Standard 2.0A	Extended 2.0B
Protocol (Mode)	Baud-Rate	10kbps ~ 1Mbps	DroneCAN
Sample-Point	50% or 87.5%		
Available SERVO ID	1 ~ 254	1 ~ 2047	1 ~ 127
Available Node ID		1 ~ 536870911	1 ~ 127
Input Signal Range	0 ~ 5V		
Connector Type	-		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	9.0 ~ 15.0V		
Operating Voltage	At 12.0V		
Operating Speed at no Load	324°/s (54RPM)		
Stall Torque	147.0kgcm (1442.1Ncm)		
Rest Current	30mA		
Running Current at no Load	500mA		
Stall Current	10000mA		
Deadband Width	-		
Travel	Travel / Command	90° / 4096	
	Servo mode	Left	Center
	Pos Command	+1366	+8192
	Pos [°]	-150	0
	Turn Mode	Left	Power On
	Pos Command	-16383	0
	Pos [°]	-359	0
	Turn Range	-32760 ~ +32760 (CAN only)	+359
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)		
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)		
Vibrations at no Load	MIL-STD-810G 514.6C-VII / EN 60068-2-6		
Connector Wire Length	400mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	64.0 x 33.0 x 90.0mm		
Weight*	500.0g		
Ball Bearing	6 Ball Bearings & 2 Needle Bearings		
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing		
Gear Material	4 Hardened Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	Square 6.5 x 6.5		
Accessories	Mounting Hardware, Servo Horn (I-MOS)		
IP-Rating	IP68		
MTTF	>1000h		
Revision & Stand	Rev. 1.2 / 01.02.2024		
Changelog	-		


*of the servo only w/o horns and accessories

SG33BL-T-CAN-12V (CIRCULAR)

#1-02346




1:2

PERFORMANCE CHART**GENERAL SPECIFICATION**


SG33BL-T-CAN-12V (Circular)			
Control System	CAN 2.0A,B / DroneCAN (UAVCAN v0)	Protocol (Mode)	Standard 2.0A
	Baud-Rate	Extended 2.0B	DroneCan
	Sample-Point	50% or 87.5%	
	Available SERVO ID	1 ~ 254	1 ~ 127
	Available Node ID	1 ~ 2047	1 ~ 536870911
	Input Signal Range	0 ~ 5V	1 ~ 127
Connector Type	Circular		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	9.0 ~ 15.0V		
Operating Voltage	At 12.0V		
Operating Speed at no Load	324°/s (54RPM)		
Stall Torque	147.0kgcm (1442.1Ncm)		
Rest Current	30mA		
Running Current at no Load	500mA		
Stall Current	10000mA		
Deadband Width	-		
Travel / Command	90° / 4096		
Servo mode	Left	Center	Rigt
Pos Command	+1366	+8192	+15018
Pos [°]	-150	0	+150
Turn Mode	Left	Power On	Right
Pos Command	-16383	0	+16383
Pos [°]	-359	0	+359
Turn Range	-32760 ~ +32760 (CAN only)		
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)		
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)		
Vibrations at no Load	MIL-STD-810G 514.6C-VII / EN 60068-2-6		
Connector Wire Length	-		
Connector Wire Gauge	-		
Connector Wire Strand Count	-		
External Dimensions	64.0 x 33.0 x 90.0mm		
Weight*	480.0g		
Ball Bearing	6 Ball Bearings & 2 Needle Bearings		
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing		
Gear Material	4 Hardened Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	Square 6.5 x 6.5		
Accessories	Mounting Hardware, Servo Horn (I-MOS)		
IP-Rating	IP68		
MTTF	>1000h		
Revision & Stand	Rev. 1.2 / 01.02.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

SG33BL-T-CAN-24V (GLAND CABLE)

#1-02464



PERFORMANCE CHART




GENERAL SPECIFICATION

SG33BL-T-CAN-24V (Gland Cable)			
Control System	CAN2.0A,B / DroneCAN (UAVCAN v0)	Standard 2.0A	Extended 2.0B
Protocol (Mode)	Protocol (Mode)	Standard 2.0A	Extended 2.0B
Baud-Rate	10kbps ~ 1Mbps		
Sample-Point	50% or 87.5%		
Available SERVO ID	1 ~ 254	1 ~ 2047	1 ~ 127
Available Node ID		1 ~ 536870911	1 ~ 127
Input Signal Range	0 ~ 5V		
Connector Type	-		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Amplifier / MCU	32Bit programmable Digital		
Operating Voltage Range	18.0 ~ 32.0V		
Operating Voltage	At 24.0V		
Operating Speed at no Load	324°/s (54RPM)		
Stall Torque	147.0kgcm (1442.1Ncm)		
Rest Current	20mA		
Running Current at no Load	230mA		
Stall Current	6400mA		
Deadband Width	-		
Travel / Command	90° / 4096		
Servo mode	Left	Center	Rigt
Pos Command	+1366	+8192	+15018
Pos [°]	-150	0	+150
Turn Mode	Left	Power On	Right
Pos Command	-16383	0	+16383
Pos [°]	-359	0	+359
Turn Range	-32760 ~ +32760 (CAN only)		
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)		
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)		
Vibrations at no Load	MIL-STD-810G 514.6C-VII / EN 60068-2-6		
Connector Wire Length	400mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	64.0 x 33.0 x 90.0mm		
Weight*	500.0g		
Ball Bearing	6 Ball Bearings & 2 Needle Bearings		
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing		
Gear Material	4 Hardened Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	Square 6.5 x 6.5		
Accessories	Mounting Hardware, Servo Horn (I-MOS)		
IP-Rating	IP68		
MTTF	>1000h		
Revision & Stand	Rev. 1.2 / 01.02.2024		
Changelog	-		


*of the servo only w/o horns and accessories

SG33BL-T-CAN-24V (CIRCULAR)

#1-02465



PERFORMANCE CHART




GENERAL SPECIFICATION


SG33BL-T-CAN-24V (Circular)			
Control System	CAN 2.0A,B / DroneCAN (UAVCAN v0)	Protocol (Mode)	Standard 2.0A
	Baud-Rate	10kbps ~ 1Mbps	Extended 2.0B
	Sample-Point	50% or 87.5%	DroneCAN
Connector Type	Circular	Available SERVO ID	1 ~ 254
Position Sensor Type	Contactless Magnetic Encoder	Available Node ID	1 ~ 2047
Motor Type	BLDC	Input Signal Range	1 ~ 127
Amplifier / MCU	32bit programmable Digital	Input Signal Range	0 ~ 5V
Operating Voltage Range	18.0 ~ 32.0V	Operating Voltage	At 24.0V
Operating Voltage	324°/s (54RPM)	Operating Speed at no Load	
Stall Torque	147.0kgcm (1442.1Ncm)	Rest Current	20mA
Running Current at no Load	230mA	Stall Current	6400mA
Stall Current	-	Deadband Width	-
Travel	Travel / Command	90° / 4096	
	Servo mode	Left	Center
	Pos Command	+1366	+8192
	Pos [°]	-150	0
	Turn Mode	Left	Power On
	Pos Command	-16383	0
	Pos [°]	-359	+16383
	Turn Range	-32760 ~ +32760 (CAN only)	+359
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)		
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)		
Vibrations at no Load	MIL-STD-810G 514.6C-VII / EN 60068-2-6		
Connector Wire Length	-		
Connector Wire Gauge	-		
Connector Wire Strand Count	-		
External Dimensions	64.0 x 33.0 x 90.0mm		
Weight*	480.0g		
Ball Bearing	6 Ball Bearings & 2 Needle Bearings		
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing		
Gear Material	4 Hardened Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	Square 6.5 x 6.5		
Accessories	Mounting Hardware, Servo Horn (I-MOS)		
IP-Rating	IP68		
MTTF	>1000h		
Revision & Stand	Rev. 1.2 / 01.02.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

SG50BL-CAN-24V(CIRCULAR)

#1-02412



1:2.5


PERFORMANCE CHART**GENERAL SPECIFICATION**

SG50BL-CAN-24V (Circular)			
Control System	CAN 2.0A,B / DroneCAN (UAVCAN v0)	Standard 2.0A	Extended 2.0B
Protocol (Mode)	Baud-Rate	10kbps ~ 1Mbps	DroneCAN
Sample-Point	50% or 87.5%		
Available SERVO ID	1 ~ 254	1 ~ 2047	1 ~ 127
Available Node ID		1 ~ 536870911	1 ~ 127
Input Signal Range	0 ~ 5V		
Connector Type	Circular		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	18.0 ~ 32.0V		
Operating Voltage	At 24.0V		
Operating Speed at no Load	120°/s (20RPM)		
Stall Torque	520.0kgcm (5101.2Ncm)		
Rest Current	45mA		
Running Current at no Load	300mA		
Stall Current	10000mA		
Deadband Width	-		
Travel	Travel / Command	90° / 4096	
	Servo mode	Left	Center
	Pos Command	+1366	+8192
	Pos [°]	-150	0
	Turn Mode	Left	Power On
	Pos Command	-16383	0
	Pos [°]	-359	0
	Turn Range	-32760 ~ +32760 (CAN only)	+359
Operating Temperature Range	-30°C ~ +70°C (-22°F ~ +158°F)		
Storage Temperature Range	-40°C ~ +80°C (-40°F ~ +176°F)		
Vibrations at no Load	MIL-STD 810G 514.6C VII / EN 60068-2-6		
Connector Wire Length	-		
Connector Wire Gauge	-		
Connector Wire Strand Count	-		
External Dimensions	100.0 x 50.0 x 105.0mm		
Weight*	1450g		
Ball Bearing	4 Angular Ball Bearings & 9 Needle Bearings		
Case Material	Rugged Aluminum Alloy With Hardcoat Anodizing		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	Square 12.0 x 12.0		
Accessories	Mounting Hardware, Servo Horn (I-MOS12)		
IP-Rating	IP68		
MTTF	>1000h		
Revision & Stand	Rev. 1.2 / 01.02.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

HSR-2645CRH


#138645

#1-02360 GP 24 Stück



1:1

PERFORMANCE CHART



GENERAL SPECIFICATION


HSR-2645CRH								
Control System	PWM							
	Pulse Width 900µs 1500µs (Center) 2100µs							
Connector Type	Hitec 3P (JR 3P compatible)							
Position Sensor Type	-							
Motor Type	Cored Carbon Brush							
Amplifier / MCU	8bit programmable Digital Amplifier with Mosfet Drive							
Operating Voltage Range	3.5V ~ 8.4V							
Operating Voltage	At 6.0V	At 7.4V						
Operating Speed at no Load	347°/s (58RPM)	435°/s (72RPM)						
Stall Torque	10.0kgcm (98.1Ncm)	12.0kgcm (117.7Ncm)						
Peak Efficiency Torque	2.0kgcm (19.6Ncm)	2.4kgcm (23.5Ncm)						
Rest Current	3mA	3mA						
Running Current at no Load	120mA	140mA						
Stall Current	2000mA	2400mA						
Deadband Width	-							
Operating Travel	<table border="1"> <tr> <td>Default</td> <td>Continuous Rotation</td> </tr> <tr> <td>Programmable</td> <td>Yes</td> </tr> <tr> <td>Multi Turn/Continuous Rotation</td> <td>Yes / Yes</td> </tr> </table>	Default	Continuous Rotation	Programmable	Yes	Multi Turn/Continuous Rotation	Yes / Yes	
Default	Continuous Rotation							
Programmable	Yes							
Multi Turn/Continuous Rotation	Yes / Yes							
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)							
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)							
Connector Wire Length	300mm							
Connector Wire Gauge	22AWG							
Connector Wire Strand Count	60/0.08							
External Dimensions	40.6 x 19.6 x 37.8mm							
Weight*	53.0g							
Ball Bearing	Dual Ball Bearing							
Case Material	Engineering Plastic							
Gear Material	1 Metal-Plastic & 3 Metal Gears							
Gear Train Backlash	Max 0.5°							
Horn Gear Spline	H24T Ø6.0							
Accessories	Mounting Hardware, Servo Horn (R-O)							
IP-Rating	IP4X							
Revision	Rev. 1.0 / 02.01.2024							
Changelog	-							

* of the servo only w/o horns and accessories


HSB-9465SH

#116465

#1-02355 GP 24 STÜCK



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**



HSB-9465SH		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 4 Slider / 1M Cycle Long Life	
Motor Type	BLDC	
Ampifier / MCU	16bit programmable Digital Amplifier with Mosfet Drive	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	667°/s (111RPM)	857°/s (143RPM)
Stall Torque	13.5kgcm (132.4Ncm)	13.5kgcm (132.4Ncm)
Peak Efficiency Torque	2.7kgcm (26.5Ncm)	2.7kgcm (26.5Ncm)
Rest Current	30mA	30mA
Running Current at no Load	250mA	250mA
Stall Current	1100mA	900mA
Deadband Width	1µs	1µs
Operating Travel	Default Programmable Multi Turn/Continuous Rotation	±60° Max. 160° n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20.0 x 37.7mm	
Weight*	62.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, HD-IM25, HD-LS25, HD-OS25, HD-X25, HD-IL25, HD-LL25	
IP-Rating	IP54	
Revision	Rev. 1.1 / 03.01.2024	
Changelog	-	

*of the servo w/o horns and accessories

HSB-9485SH

#116485

#1-02356 GP 24 STÜCK

**PERFORMANCE CHART****GENERAL SPECIFICATION**

HSB-9485SH		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 4 Slider / 1M Cycle Long Life	
Motor Type	BLDC	
Amplifier / MCU	16bit programmable Digital Amplifier with Mosfet Drive	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	333°/s (56RPM)	400°/s (67RPM)
Stall Torque	26.0kgcm (255.1Ncm)	26.0kgcm (255.1Ncm)
Peak Efficiency Torque	5.2kgcm (51.0Ncm)	5.2kgcm (51.0Ncm)
Rest Current	30mA	30mA
Running Current at no Load	360mA	430mA
Stall Current	1300mA	1100mA
Deadband Width	1µs	1µs
Operating Travel	Default	±60°
	Programmable	Max. 160° **
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20.0 x 37.7mm	
Weight*	62.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25, HD-IL25, HD-L25)	
IP-Rating	IP54	
Revision	Rev. 1.1 / 03.01.2024	
Changelog	-	


*of the servo w/o horns and accessories

** also available with 270°


HSB-9381TH

#1-00074

#1-02357 GP 24 Stück



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**



HSB-9381TH		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 4 Slider / 1M Cycle Long Life	
Motor Type	BLDC	
Amplifier / MCU	16bit programmable Digital	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	353°/s (59RPM)	429°/s (71RPM)
Stall Torque	34.0kgcm (333.5Ncm)	34.0kgcm (333.5Ncm)
Peak Efficiency Torque	6.8kgcm (66.7Ncm)	6.8kgcm (66.7Ncm)
Rest Current	27mA	27mA
Running Current at no Load	250mA	250mA
Stall Current	2700mA	2100mA
Deadband Width	1µs	1µs
Operating Travel	Default Programmable Multi Turn/Continuous Rotation	±60° Max. 160° n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20.0 x 38.0mm	
Weight*	79.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Aluminum Alloy	
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears	
Gear Train Backlash	Max 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)	
IP-Rating	IP54	
Revision	Rev. 1.1 / 03.01.2024	
Changelog	-	

*of the servo w/o horns and accessories

HSB-M9381TH

#1-01191

#1-02353 GP 24 Stück



**PERFORMANCE CHART****GENERAL SPECIFICATION**

HSB-M9381TH		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	BLDC	
Amplifier / MCU	16bit programmable Digital Amplifier with Mosfet Drive	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	353°/s (59RPM)	429°/s (71RPM)
Stall Torque	34.0kgcm (333.5Ncm)	34.0kgcm (333.5Ncm)
Peak Efficiency Torque	6.8kgcm (66.7Ncm)	6.8kgcm (66.7Ncm)
Rest Current	27mA	27mA
Running Current at no Load	250mA	250mA
Stall Current	2700mA	2100mA
Deadband Width	1µs	1µs
Operating Travel	Default	±60°
	Programmable	Max. 300°
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +70°C (-4°F ~ +158°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20.0 x 38.0mm	
Weight*	78.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Aluminum Alloy	
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears	
Gear Train Backlash	Max 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)	
IP-Rating	IP54	
Revision	Rev. 1.1 / 03.01.2024	
Changelog	-	

*of the servo w/o horns and accessories

DB950SW



1-03218

GENERAL SPECIFICATION

DB950SW			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contact Analog Potentiometer		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	4.8V	6.0V	7.4V
No Load Speed	0.23sec/60°	0.18sec/60°	0.14sec/60°
Stall Torque	35.0kgf·cm (486.06oz·in)	40.0kgf·cm (555.5 oz·in)	40.0kgf·cm (555.5 oz·in)
Peak Efficiency Torque	7.0kgf·cm (97.21oz·in)	8.0kgf·cm (111.1 oz·in)	8.0kgf·cm (111.1 oz·in)
Standing Current	35mA	35mA	35mA
No Load Running Current	350mA	350mA	350mA
Stall Current	5,000mA	5,000mA	4,200mA
Deadband	1µs	1µs	1µs
Operating Travel	Default: ±60°, Programmable: Max 175° / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 38.5mm (1.575inch x 0.787inch x 1.516inch)		
Weight	68.0g (2.399oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic & Aluminum Heat Sink		
Gear Material	1 Metal-Plastic & 3 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP54		
Servo Amplifier Type	32bit Programmable Digital		

DB951WP



1-03088

GENERAL SPECIFICATION

DB951WP			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contact Analog Potentiometer		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.12sec/60°	0.10sec/60°
Stall Torque	-	38.0kgf-cm (527.72oz-in)	38.0kgf-cm (527.72oz-in)
Peak Efficiency Torque	-	7.6kgf-cm (105.54oz-in)	7.6kgf-cm (105.54oz-in)
Standing Current	-	35mA	35mA
No Load Running Current	-	350mA	350mA
Stall Current	-	8,000mA	6,500mA
Deadband	-	1µs	1µs
Operating Travel	Default: ±60°, Programmable: Max 260° / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	90.0g (3.175oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	16bit programmable Digital		

DB961WP

#1-02571


**PERFORMANCE CHART****GENERAL SPECIFICATION**

DB961WP		
Control System	PWM / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	BLDC	
Amplifier / MCU	16bit programmable Digital	
Operating Voltage Range	4.0 ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	333°/s (56RPM)	400°/s (67RPM)
Stall Torque	55.0kgcm (539.6Ncm)	55.0kgcm (539.6Ncm)
Peak Efficiency Torque	11.0kgcm (107.9Ncm)	11.0kgcm (107.9Ncm)
Rest Current	35mA	35mA
Running Current at no Load	500mA	500mA
Stall Current	8000mA	6500mA
Deadband Width	1µs	1µs
Operating Travel	Default	±60°
	Programmable	Max. 260°
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	MIL-STD-810G 514.6C-VII	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20.0 x 39.0mm	
Weight*	90.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Aluminum Alloy	
Gear Material	5 Hardened Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, HD-IM25, HD-LS25, HD-OS25, HD-X25	
IP-Rating	IP67	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	


*of the servo only w/o horns and accessories

DB778WP

#1-02853



1:1



PERFORMANCE CHART**GENERAL SPECIFICATION**

DB778WP		
Control System	PWM / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	BLDC	
Amplifier / MCU	32bit programmable Digital	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V At 7.4V	
Operating Speed at no Load	500°/s (83RPM) 600°/s (100RPM)	
Stall Torque	15.0kgcm (147.2Ncm) 18.0kgcm (175.6Ncm)	
Peak Efficiency Torque	3.0kgcm (29.4Ncm) 3.6kgcm (35.3Ncm)	
Rest Current	28mA 28mA	
Running Current at no Load	500mA 600mA	
Stall Current	3500mA 4500mA	
Deadband Width	1µs 1µs	
Operating Travel	Default ±60°	
	Programmable Max. 175°	
	Multi Turn/Continuous Rotation n/a / n/a	
Operating Temperature Range	-20°C ~ +70°C (-4°F ~ +158°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	200mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	41.0 x 21.0 x 26.5mm	
Weight*	66.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Rugged Aluminum Alloy	
Gear Material	5 Hardened Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Hex Screw, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)	
IP-Rating	IP67	
Revision	Rev. 1.0 / 09.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories

DBX961WP


1-03226

GENERAL SPECIFICATION


DBX961WP			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contact Analog Potentiometer		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.18sec/60°	0.15sec/60°
Stall Torque	-	55.0kgf·cm (763.81oz·in)	55.0kgf·cm (763.81oz·in)
Peak Efficiency Torque	-	11.0kgf·cm (152.76oz·in)	11.0kgf·cm (152.76oz·in)
Standing Current	-	35mA	35mA
No Load Running Current	-	500mA	500mA
Stall Current	-	8,000mA	6,500mA
Deadband	-	1μs	1μs
Operating Travel	Default: ±60°, Programmable: Max 260° / Pulse Width: 900~2100μs(Center:1500μs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 40.8mm (1.575inch x 0.787inch x 1.606inch)		
Weight	106.7g (3.764oz)		
Bearing Type	2 Ball Bearing		
Case Material	Rugged Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	16bit programmable Digital		

MDB941WP-CAN

1-03191





1:1

**GENERAL SPECIFICATION**

MDB941WP-CAN			
Control System	CAN 2.0A,B		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.085sec/60°	0.07sec/60°
Stall Torque	-	20.6kgf·cm (286.08oz·in)	25.4kgf·cm (352.74oz·in)
Peak Efficiency Torque	-	4.1kgf·cm (56.94oz·in)	5.1kgf·cm (70.83oz·in)
Standing Current	-	30mA	30mA
No Load Running Current	-	500mA	500mA
Stall Current	-	8,000mA	8,000mA
Deadband	-	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable) / Turn Mode : ±32760 Turns		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	91.7g (3.235oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	32bit programmable Digital		

MDB950SW-CAN



1-03093

GENERAL SPECIFICATION

MDB950SW-CAN			
Control System	CAN 2.0A,B		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	4.8V	6.0V	7.4V
No Load Speed	0.23sec/60°	0.18sec/60°	0.14sec/60°
Stall Torque	35.0kgf-cm (486.06oz-in)	40.0kgf-cm (555.5 oz-in)	40.0kgf-cm (555.5 oz-in)
Peak Efficiency Torque	7.0kgf-cm (97.21oz-in)	8.0kgf-cm (111.1 oz-in)	8.0kgf-cm (111.1 oz-in)
Standing Current	30mA	30mA	30mA
No Load Running Current	350mA	350mA	350mA
Stall Current	5,000mA	5,000mA	4,200mA
Deadband	n/a	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable) / Turn Mode : ±32760 Turns		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 38.5mm (1.575inch x 0.787inch x 1.516inch)		
Weight	70.7g (2.494oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic & Aluminum Heat Sink		
Gear Material	1 Metal-Plastic & 3 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP54		
Servo Amplifier Type	32bit programmable Digital		

MDB961WP-CAN

1-03004




GENERAL SPECIFICATION


MDB961WP-CAN			
Control System	CAN 2.0A,B		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.18sec/60°	0.15sec/60°
Stall Torque	-	55.0kgf-cm (763.81oz-in)	55.0kgf-cm (763.81oz-in)
Peak Efficiency Torque	-	11.0kgf-cm (152.76oz-in)	11.0kgf-cm (152.76oz-in)
Standing Current	-	30mA	30mA
No Load Running Current	-	500mA	500mA
Stall Current	-	8,000mA	6,500mA
Deadband	-	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable) / Turn Mode : ±32760 Turns		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	90.0g (3.175oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	32bit programmable Digital		

MDB961WP-CAN 28V

#1-03003





1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**

MDB961WP-CAN 28V			
Control System	CAN BUS	Protocol (Mode)	Standard 2.0A
		Baud-Rate	10kbps ~ 1Mbps
		Sample-Point	50% or 87.5%
	Available SERVO ID	1 ~ 254	1 ~ 127
	Available Node ID	1 ~ 2047	1 ~ 536870911
	Input Signal Range	0 ~ 5V	1 ~ 127
Connector Type	Hitec 4P		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	8.0V ~ 32.0V	At 12.0V	At 24.0V
Operating Voltage		At 24.0V	At 28.0V
Operating Speed at no Load	429°/s (71RPM)	429°/s (71RPM)	429°/s (71RPM)
Stall Torque	60.0kgcm (588.6Ncm)	60.0kgcm (588.6Ncm)	60.0kgcm (588.6Ncm)
Peak Efficiency Torque	12.0kgcm (117.7Ncm)	12.0kgcm (117.7Ncm)	12.0kgcm (117.7Ncm)
Rest Current	18mA	10mA	9mA
Running Current at no Load	500mA	300mA	200mA
Stall Current	6700mA	3400mA	3000mA
Deadband Width	n/a	n/a	n/a
Travel	Travel / Command	90° / 4096	
	Servo mode	Left	Center
	Pos Command	+1366	+8192
	Pos [°]	-150	0
	Turn Mode	Left	Power On
	Pos Command	-16383	0
	Pos [°]	-359	0
	Turn Range	-32760 ~ +32760	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	40.0 x 20.0 x 39.0mm		
Weight*	90.0g		
Ball Bearing	Dual Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-OS25, HD-X25)		
IP-Rating	IP67		
Revision	Rev. 1.0 / 09.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

MDB1200WP

#1-03109



GENERAL SPECIFICATION**PERFORMANCE CHART**

MDB1200WP		
Control System	PWM / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	BLDC	
Amplifier / MCU	32bit programmable Digital	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V At 7.0V	
Operating Speed at no Load	273°/s (46RPM) 333°/s (56RPM)	
Stall Torque	100.0kgcm (981.0Ncm) 110.0kgcm (1079.1Ncm)	
Peak Efficiency Torque	20.0kgcm (196.2Ncm) 22.0kgcm (215.8Ncm)	
Rest Current	20mA 20mA	
Running Current at no Load	500mA 550mA	
Stall Current	5000mA 4300mA	
Deadband Width	2µs 2µs	
	Default ±60°	
Operating Travel	Programmable Max. 320°	
	Multi Turn/Continuous Rotation n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	62.0 x 30.0 x 47.0mm	
Weight*	260g	
Ball Bearing	2 Ball Bearing & 2 Needle Bearing	
Case Material	Aluminum Alloy	
Gear Material	5 Hardened Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H15T Ø8.0	
Accessories	Mounting Hardware, Servo Horns (Q-OA15, Q-XA15)	
IP-Rating	IP67	
Revision	Rev. 1.0 / 09.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories

MDB961WP



1-03225

GENERAL SPECIFICATION

MDB961WP			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V	6.0V	7.4V
Voltage	-	6.0V	7.4V
No Load Speed	-	0.18sec/60°	0.15sec/60°
Stall Torque	-	55.0kgf·cm (763.81oz·in)	55.0kgf·cm (763.81oz·in)
Peak Efficiency Torque	-	11.0kgf·cm (152.76oz·in)	11.0kgf·cm (152.76oz·in)
Standing Current	-	35mA	35mA
No Load Running Current	-	500mA	500mA
Stall Current	-	8,000mA	6,500mA
Deadband	-	1µs	1µs
Operating Travel	Default: ±60°, Programmable: Max 320° / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	90.0g (3.175oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	16bit programmable Digital		

MDB89MH

1-03276


GENERAL SPECIFICATION

MDB89MH			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.17sec/60°	0.13sec/60°
Stall Torque	-	10.5kgf·cm (145.82oz·in)	12.5kgf·cm (173.59oz·in)
Peak Efficiency Torque	-	2.1kgf·cm (29.16oz·in)	2.5kgf·cm (34.72oz·in)
Standing Current	-	30mA	30mA
No Load Running Current	-	150mA	170mA
Stall Current	-	2,400mA	3,000mA
Deadband	-	2µs	2µs
Operating Travel	Default: ±60°, Programmable: Max 175° / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	240mm (9.449inch)		
Connector Wire Gauge	22AWG		
Dimensions	29.0mm x 13.0mm x 34.0mm (1.142inch x 0.512inch x 1.339inch)		
Weight	33.6g (1.185oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	5 Metal Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP4X		
Servo Amplifier Type	32bit Programmable Digital		


MDB-777WP-CAN/DRONECAN

#1-03030 #1-03031

GENERAL SPECIFICATION




PERFORMANCE CHART



MDB777WP-CAN/DroneCAN					
Control System	CAN BUS	Standard 2.0A	Extended 2.0B		
	Protocol (Mode)	10kbps ~ 1Mbps	DroneCAN		
	Baud-Rate	50% or 87.5%			
	Sample-Point	Available SERVO ID	1 ~ 254		
		Available Node ID	1 ~ 2047		
		Input Signal Range	1 ~ 127		
		0 ~ 5V	1 ~ 127		
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	BLDC				
Amplifier / MCU	32bit programmable Digital				
Operating Voltage Range	4.0V ~ 8.4V				
Operating Voltage	At 6.0V	At 7.4V			
Operating Speed at no Load	750°/s (125RPM)	1000°/s (167RPM)			
Stall Torque	8.0kgcm (78.5Ncm)	11.0kgcm (107.9Ncm)			
Peak Efficiency Torque	1.6kgcm (15.7Ncm)	2.2kgcm (21.6Ncm)			
Rest Current	26mA	26mA			
Running Current at no Load	320mA	350mA			
Stall Current	4000mA	5000mA			
Deadband Width	n/a	n/a			
Travel	Travel / Command	90° / 4096			
	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	-				
Connector Wire Length	300mm				
Connector Wire Gauge	20AWG				
Connector Wire Strand Count	80/0.08				
External Dimensions	41.0 x 21.0 x 26.5mm				
Weight*	70.0g				
Ball Bearing	Dual Ball Bearing				
Case Material	Aluminum Alloy				
Gear Material	5 Hardened Steel Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	H25T Ø6.0				
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)				
IP-Rating	IP67				
Revision	Rev. 1.0 / 09.01.2024				
Changelog	-				
*of the servo only w/o horns and accessories					


MDB778WP-CAN/DRONECAN

#1-03032 #1-03033



1:2

PERFORMANCE CHART





GENERAL SPECIFICATION

MDB778WP-CAN/DroneCAN					
Control System	CAN BUS	Standard 2.0A	Extended 2.0B		
	Protocol (Mode)	10kbps ~ 1Mbps	DroneCAN		
	Baud-Rate	50% or 87.5%			
	Sample-Point	1 ~ 254	1 ~ 127		
	Available SERVO ID	1 ~ 2047	1 ~ 536870911		
	Available Node ID		1 ~ 127		
	Input Signal Range	0 ~ 5V			
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	BLDC				
Amplifier / MCU	32bit programmable Digital				
Operating Voltage Range	4.0V ~ 8.4V				
Operating Voltage	At 6.0V	At 7.4V			
Operating Speed at no Load	462°/s (77RPM)	600°/s (100RPM)			
Stall Torque	14.0kgcm (137.3Ncm)	16.0kgcm (157.0Ncm)			
Peak Efficiency Torque	2.8kgcm (27.5Ncm)	3.3kgcm (32.4Ncm)			
Rest Current	50mA	50mA			
Running Current at no Load	400mA	500mA			
Stall Current	4000mA	5000mA			
Deadband Width	n/a	n/a			
Travel	Travel / Command	90° / 4096			
	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	-				
Connector Wire Length	300mm				
Connector Wire Gauge	20AWG				
Connector Wire Strand Count	80/0.08				
External Dimensions	41.0 x 21.0 x 26.5mm				
Weight*	70.0g				
Ball Bearing	Dual Ball Bearing				
Case Material	Aluminum Alloy				
Gear Material	5 Hardened Steel Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	H25T Ø6.0				
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)				
IP-Rating	IP67				
Revision	Rev. 1.0 / 09.01.2024				
Changelog	-				
*of the servo only w/o horns and accessories					

MDB941WP-DRONECAN



1-03314

GENERAL SPECIFICATION

MDB941WP-DroneCAN			
Control System	DroneCAN (UAVCAN v0)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.085sec/60°	0.07sec/60°
Stall Torque	-	20.6kgf·cm (286.08oz·in)	25.4kgf·cm (352.74oz·in)
Peak Efficiency Torque	-	4.1kgf·cm (56.94oz·in)	5.1kgf·cm (70.83oz·in)
Standing Current	-	30mA	30mA
No Load Running Current	-	500mA	500mA
Stall Current	-	8,000mA	8,000mA
Deadband	-	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	91.7g (3.235oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	32bit programmable Digital		

MDB950SW-DRONECAN

1-03313



GENERAL SPECIFICATION

MDB950SW-DroneCAN			
Control System	DroneCAN (UAVCAN v0)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	4.8V	6.0V	7.4V
No Load Speed	0.23sec/60°	0.18sec/60°	0.14sec/60°
Stall Torque	35.0kgf-cm (486.06oz-in)	40.0kgf-cm (555.5 oz-in)	40.0kgf-cm (555.5 oz-in)
Peak Efficiency Torque	7.0kgf-cm (97.21oz-in)	8.0kgf-cm (111.1 oz-in)	8.0kgf-cm (111.1 oz-in)
Standing Current	30mA	30mA	30mA
No Load Running Current	350mA	350mA	350mA
Stall Current	5,000mA	5,000mA	4,200mA
Deadband	n/a	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 38.5mm (1.575inch x 0.787inch x 1.516inch)		
Weight	70.7g (2.494oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic & Aluminum Heat Sink		
Gear Material	1 Metal-Plastic & 3 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP54		
Servo Amplifier Type	32bit programmable Digital		

MDB961WP-UAVCAN / DRONECAN

1-03228



GENERAL SPECIFICATION



MDB961WP-UAVCAN / DroneCAN			
Control System	DroneCAN (UAVCAN v0)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	4.0 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.18sec/60°	0.15sec/60°
Stall Torque	-	55.0kgf·cm (763.81oz·in)	55.0kgf·cm (763.81oz·in)
Peak Efficiency Torque	-	11.0kgf·cm (152.76oz·in)	11.0kgf·cm (152.76oz·in)
Standing Current	-	30mA	30mA
No Load Running Current	-	500mA	500mA
Stall Current	-	8,000mA	6,500mA
Deadband	-	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	90.0g (3.175oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	32bit programmable Digital		

MDB961WP-UAVCAN/DRONECAN-28V

1-03229



GENERAL SPECIFICATION

MDB961WP-UAVCAN/DroneCAN-28V			
Control System	DroneCAN (UAVCAN v0)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	BLDC		
Operating Voltage Range	8.0 ~ 32.0V		
Voltage	12.0V	24.0V	28.0V
No Load Speed	0.14sec/60°	0.14sec/60°	0.14sec/60°
Stall Torque	60.0kgf·cm (833.24oz·in)	60.0kgf·cm (833.24oz·in)	60.0kgf·cm (833.24oz·in)
Peak Efficiency Torque	12.0kgf·cm (166.65oz·in)	12.0kgf·cm (166.65oz·in)	12.0kgf·cm (166.65oz·in)
Standing Current	20mA	12mA	11mA
No Load Running Current	500mA	300mA	200mA
Stall Current	6,700mA	3,400mA	3,000mA
Deadband	n/a	n/a	n/a
Operating Travel	Servo Mode : ±60°(Default), ±150°(Programmable)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	40.0mm x 20.0mm x 39.0mm (1.575inch x 0.787inch x 1.535inch)		
Weight	90.0g (3.175oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Hardened Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP67		
Servo Amplifier Type	32bit programmable Digital		

MD65MG-CAN/UAV/DRONECAN



PERFORMANCE CHART




1:1

GENERAL SPECIFICATION

MD65MG-CAN/UAVCAN/DroneCAN					
Control System	CAN BUS	Standard 2.0A	Extended 2.0B		
	Protocol (Mode)	10kbps ~ 1Mbps	UAVCAN/DroneCAN		
	Baud-Rate	50% or 87.5%			
	Sample-Point	Available SERVO ID	1 ~ 254		
		Available Node ID	1 ~ 2047		
		Input Signal Range	0 ~ 5V		
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	Cored Metal Brush				
Amplifier / MCU	32bit programmable Digital				
Operating Voltage Range	4.0V ~ 8.4V	At 4.8V	At 6.0V		
Operating Voltage					
Operating Speed at no Load	429°/s (71RPM)	546°/s (91RPM)			
Stall Torque	1.8kgcm (17.7Ncm)	2.2kgcm (21.6Ncm)			
Peak Efficiency Torque	0.4kgcm (3.9Ncm)	0.4kgcm (3.9Ncm)			
Rest Current	30mA	30mA			
Running Current at no Load	180mA	220mA			
Stall Current	960mA	1200mA			
Deadband Width	4Step	4Step			
Travel	Travel / Command	90° / 4096			
	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	MIL-STD-810G 514.6C-VII				
Connector Wire Length	300mm				
Connector Wire Gauge	28AWG				
Connector Wire Strand Count	20/0.08				
External Dimensions	23.6 x 11.6 x 24.0mm				
Weight*	12.8g				
Ball Bearing	Single Ball Bearing				
Case Material	Engineering Plastic				
Gear Material	1 Heavy Duty Resin & 4 Metal Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	25T Ø5.0				
Accessories	Tapping Screw, Servo Horns (MS-I25, MS-L25, MS-X25)				
IP-Rating	IP4X				
Revision	Rev. 1.1 / 03.01.2024				
Changelog	-				
*of the servo only w/o horns and accessories					


MD70MH-CAN/UVCAN/DRONECAN

#1-01201,#1-01644



1:1


PERFORMANCE CHART



GENERAL SPECIFICATION


MD70MH-CAN/UVCAN/DroneCAN					
Control System	Protocol (Mode)	Standard 2.0A	Extended 2.0B		
	Baud-Rate	10kbps ~ 1Mbps	UVCAN/DroneCAN		
	Sample-Point	50% or 87.5%			
	Available SERVO ID	1 ~ 254	1 ~ 127		
	Available Node ID	1 ~ 2047	1 ~ 536870911		
	Input Signal Range	0 ~ 5V	1 ~ 127		
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	Cored Metal Brush				
Amplifier / MCU	32bit programmable Digital				
Operating Voltage Range	4.0V ~ 8.4V				
Operating Voltage	At 6.0V	At 7.4V			
Operating Speed at no Load	400°/s (67RPM)	500°/s (83RPM)			
Stall Torque	3.1kgcm (30.4Ncm)	3.8kgcm (37.3Ncm)			
Peak Efficiency Torque	0.6kgcm (5.9Ncm)	0.8kgcm (7.9Ncm)			
Rest Current	30mA	30mA			
Running Current at no Load	200mA	240mA			
Stall Current	1000mA	1300mA			
Deadband Width	n/a	n/a			
Travel	Travel / Command	90° / 4096			
	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	-				
Connector Wire Length	300mm				
Connector Wire Gauge	28AWG				
Connector Wire Strand Count	20/0.08				
External Dimensions	23.4 x 11.4 x 24.0mm				
Weight*	14.1g				
Ball Bearing	Single Ball Bearing				
Case Material	Engineering Plastic				
Gear Material	1 Heavy Duty Resin & 4 Metal Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	25T Ø5.0				
Accessories	Tapping Screw, Servo Horns (MS-I25, MS-L25, MS-X25)				
Dust & Water Protection class	IP4X				
Revision	Rev. 1.1 / 03.01.2024				
Changelog	-				
*of the servo only w/o horns and accessories					

MD85MG-CAN/UAVCAN/DRONECAN



1:1

PERFORMANCE CHART




GENERAL SPECIFICATION

MD85MG-CAN/UAVCAN/DroneCAN					
Control System	CAN BUS	Standard 2.0A	Extended 2.0B		
	Protocol (Mode)	10kbps ~ 1Mbps	UAVCAN/DroneCAN		
	Baud-Rate	50% or 87.5%			
	Sample-Point	Available SERVO ID	1 ~ 254		
	Available Node ID	1 ~ 2047	1 ~ 127		
	Input Signal Range	0 ~ 5V			
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	Cored Carbon Brush				
Amplifier / MCU	32bit programmable Digital with Mosfet Drive				
Operating Voltage Range	4.0V ~ 8.4V	At 4.8V	At 6.0V		
Operating Voltage					
Operating Speed at no Load	353°/s (59RPM)	462°/s (77RPM)			
Stall Torque	3.6kgcm (35.3Ncm)	4.3kgcm (42.2Ncm)			
Peak Efficiency Torque	0.7kgcm (6.9Ncm)	0.9kgcm (8.8Ncm)			
Rest Current	30mA	30mA			
Running Current at no Load	260mA	300mA			
Stall Current	1300mA	1600mA			
Deadband Width	4Step	4Step			
Travel	Travel / Command	90° / 4096			
	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	MIL-STD-810G 514.6C-VII				
Connector Wire Length	300mm				
Connector Wire Gauge	28AWG				
Connector Wire Strand Count	20/0.08				
External Dimensions	29.0 x 13.0 x 29.4mm				
Weight*	22.7g				
Ball Bearing	Single Ball Bearing				
Case Material	Engineering Plastic				
Gear Material	5 Metal Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	24T Ø6.0				
Accessories	Mounting Hardware, Servo Horns (M-I, M-X, M-O)				
IP-Rating	IP4X				
Revision	Rev. 1.1 / 03.01.2024				
Changelog	-				


*of the servo only w/o horns and accessories

MD89MW-CAN/UAVCAN/DRONECAN

#1-01972,#1-01973

GENERAL SPECIFICATION



1:1

PERFORMANCE CHART

MD89MW-CAN/UAVCAN/DroneCAN				
Control System	CAN BUS	Standard 2.0A Extended 2.0B UAVCAN/DroneCAN		
	Protocol (Mode)	Standard 2.0A	Extended 2.0B	
	Baud-Rate	10kbps ~ 1Mbps		
	Sample-Point	50% or 87.5%		
	Available SERVO ID	1 ~ 254	1 ~ 127	
	Available Node ID	1 ~ 2047	1 ~ 536870911	
	Input Signal Range	0 ~ 5V	1 ~ 127	
Connector Type	Hitec 4P			
Position Sensor Type	Contactless Magnetic Encoder			
Motor Type	Coreless			
Amplifier / MCU	32bit programmable Digital			
Operating Voltage Range	4.0 ~ 8.4V			
Operating Voltage	At 4.8V At 6.0V At 7.4V			
Operating Speed at no Load	353°/s (59RPM)	462°/s (77RPM)	546°/s (91RPM)	
Stall Torque	5.3kgcm (52.0Ncm)	6.4kgcm (62.8Ncm)	8.5kgcm (83.4Ncm)	
Peak Efficiency Torque	1.1kgcm (10.8Ncm)	1.3kgcm (12.8Ncm)	1.7kgcm (16.7Ncm)	
Rest Current	30mA	30mA	30mA	
Running Current at no Load	200mA	250mA	300mA	
Stall Current	1800mA	2200mA	2700mA	
Deadband Width	n/a	n/a	n/a	
Travel	Travel / Command Servo mode Pos Command Pos [°] Turn Mode Pos Command Pos [°] Turn Range	90° / 4096 Left +1366 -150 Left -16383 -359 -32760 ~ +32760 (CAN only)	Center +8192 0 Power On Right 0 0 +359	Rigt +15018 +150 Right +16383 +359
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)			
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)			
Vibrations at no Load	-			
Connector Wire Length	300mm			
Connector Wire Gauge	22AWG			
Connector Wire Strand Count	60/0.08			
External Dimensions	28.9 x 13.0 x 30.0mm			
Weight*	28.0g			
Ball Bearing	Dual Ball Bearing			
Case Material	Engineering Plastic			
Gear Material	5 Metal Gears			
Gear Train Backlash	Max. 0.5°			
Horn Gear Spline	25T Ø6.0			
Accessories	Mounting Hardware, Servo Horns (M-I, M-X, M-O)			
IP-Rating	IP4X			
Revision	Rev. 1.1 / 03.01.2024			
Changelog	-			
*of the servo only w/o horns and accessories				

MD145SW-CAN/UAVCAN/DRONECAN

#1-01787,#1-01641



GENERAL SPECIFICATION**PERFORMANCE CHART**

MD145SW-CAN/UAVCAN/DroneCAN					
Control System	Protocol (Mode)	Standard 2.0A	Extended 2.0B		
	Baud-Rate	10kbps ~ 1Mbps	UAVCAN/DroneCAN		
	Sample-Point	50% or 87.5%			
	Available SERVO ID	1 ~ 254	1 ~ 127		
	Available Node ID	1 ~ 2047	1 ~ 536870911		
	Input Signal Range	0 ~ 5V	1 ~ 127		
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	Cored Carbon Brush				
Amplifier / MCU	32bit programmable Digital				
Operating Voltage Range	4.0V ~ 8.4V				
Operating Voltage	At 4.8V	At 6.0V	At 7.4V		
Operating Speed at no Load	286°/s (48RPM)	353°/s (59RPM)	429°/s (71RPM)		
Stall Torque	4.9kgcm (16.7Ncm)	5.9kgcm (57.9Ncm)	7.0kgcm (68.7Ncm)		
Peak Efficiency Torque	1.0kgcm (9.8Ncm)	1.2kgcm (11.8Ncm)	1.4kgcm (13.7Ncm)		
Rest Current	30mA	30mA	30mA		
Running Current at no Load	120mA	180mA	180mA		
Stall Current	1,600mA	2,500mA	2,500mA		
Deadband Width	4Step	4Step	4Step		
Travel / Command	90° / 4096				
Travel	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	MIL-STD-810G 514.6C-VII				
Connector Wire Length	300mm				
Connector Wire Gauge	24AWG				
Connector Wire Strand Count	40/0.08				
External Dimensions	30.0 x 10.0 x 37.0mm				
Weight*	27.6g				
Ball Bearing	Dual Ball Bearing				
Case Material	Engineering Plastic				
Gear Material	1 Metal-Plastic & 4 Steel Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	25T Ø5.0				
Accessories	Mounting Hardware, Servo Horns (MS-L25, MS-ML25)				
IP-Rating	IP4X				
Revision	Rev. 1.1 / 03.01.2024				
Changelog	-				
*of the servo only w/o horns and accessories					

MD245MW-CAN/UAVCAN/DRONECAN


#1-01574,#1-01642

GENERAL SPECIFICATION



1:1

PERFORMANCE CHART




MD245MW-CAN/UAVCAN/DroneCAN					
Control System	CAN BUS	Standard 2.0A	Extended 2.0B		
	Protocol (Mode)	10kbps ~ 1Mbps	UAVCAN/DroneCAN		
	Baud-Rate	Sample-Point	50% or 87.5%		
	Available SERVO ID	1 ~ 254	1 ~ 127		
	Available Node ID	1 ~ 2047	1 ~ 536870911		
	Input Signal Range	0 ~ 5V	1 ~ 127		
Connector Type	Hitec 4P				
Position Sensor Type	Contactless Magnetic Encoder				
Motor Type	Coreless Metal Brush				
Amplifier / MCU	32bit programmable Digital				
Operating Voltage Range	4.0V ~ 8.4V				
Operating Voltage	At 4.8V	At 6.0V	At 7.4V		
Operating Speed at no Load	353°/s (59RPM)	462°/s (77RPM)	546°/s (91RPM)		
Stall Torque	4.2kgcm (41.2Ncm)	5.2kgcm (51.0Ncm)	6.4kgcm (62.8Ncm)		
Peak Efficiency Torque	0.8kgcm (7.9Ncm)	1.0kgcm (9.8Ncm)	1.3kgcm (12.8Ncm)		
Rest Current	30mA	30mA	30mA		
Running Current at no Load	110mA	150mA	190mA		
Stall Current	1000mA	1300mA	1600mA		
Deadband Width	n/a	n/a	n/a		
Travel	Travel / Command	90° / 4096			
	Servo mode	Left	Center		
	Pos Command	+1366	+8192		
	Pos [°]	-150	0		
	Turn Mode	Left	Power On		
	Pos Command	-16383	0		
	Pos [°]	-359	0		
	Turn Range	-32760 ~ +32760 (CAN only)			
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)				
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)				
Vibrations at no Load	MIL-STD-810G 514.6C-VII				
Connector Wire Length	300mm				
Connector Wire Gauge	22AWG				
Connector Wire Strand Count	60/0.08				
External Dimensions	32.4 x 16.8 x 32.8mm				
Weight*	35.5g				
Ball Bearing	Dual Ball Bearing				
Case Material	Engineering Plastic				
Gear Material	1 Metal-Plastic & 3 Metal Gears				
Gear Train Backlash	Max. 0.5°				
Horn Gear Spline	H25T Ø6.0				
Accessories	Mounting Hardware, Servo Horn (M-O25)				
IP-Rating	IP4X				
Revision	Rev. 1.1 / 03.01.2024				
Changelog	-				
*of the servo only w/o horns and accessories					

MD250MW-CAN/UAVCAN/DRONECAN


#1-01666,#1-01572

GENERAL SPECIFICATION



1:1



PERFORMANCE CHART



MD250MW-CAN/UAVCAN/DroneCAN			
Control System	CAN BUS	Standard 2.0A	Extended 2.0B
	Protocol (Mode)	10kbps ~ 1Mbps	UAVCAN/DroneCAN
	Baud-Rate	50% or 87.5%	
	Sample-Point	1 ~ 254	1 ~ 127
	Available SERVO ID	1 ~ 2047	1 ~ 536870911
	Available Node ID		1 ~ 127
	Input Signal Range	0 ~ 5V	
Connector Type	Hitec 4P		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	4.0V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	300°/s (50RPM)	375°/s (63RPM)	462°/s (77RPM)
Stall Torque	4.9kgcm (48.1Ncm)	6.1kgcm (59.8Ncm)	7.5kgcm (73.6Ncm)
Peak Efficiency Torque	1.0kgcm (9.8Ncm)	1.2kgcm (11.8Ncm)	1.5kgcm (14.7Ncm)
Rest Current	40mA	40mA	40mA
Running Current at no Load	110mA	150mA	190mA
Stall Current	1000mA	1300mA	1600mA
Travel / Command	90° / 4096		
Servo mode	Left	Center	Rigt
Pos Command	+1366	+8192	+15018
Pos [°]	-150	0	+150
Turn Mode	Left	Power On	Right
Pos Command	-16383	0	+16383
Pos [°]	-359	0	+359
Turn Range	-32760 ~ +32760 (CAN only)		
Operating Temperature Range	-20°C ~ +60°C (-22°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +60°C (-80°F ~ +176°F)		
Vibrations at no Load	MIL-STD-810G 514.6C-VII		
Connector Wire Length	300mm		
Connector Wire Gauge	22AWG		
Connector Wire Strand Count	60/0.08		
External Dimensions	35.4 x 15.0 x 32.0mm		
Weight*	38.8g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Metal-Plastic & 4 Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horn (M-I25)		
IP-Rating	IP4X		
Revision	Rev. 1.1 / 03.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			


MD950TW-CAN/UVCAN/DRONECAN

#1-01646,#1-01647



1:1

PERFORMANCE CHART



MD950TW-CAN/UVCAN



— current [mA] — speed [°/s]

GENERAL SPECIFICATION

MD950TW-CAN/UVCAN			
Control System	CAN BUS		
	Protocol (Mode)	Standard 2.0A	Extended 2.0B
	Baud-Rate	10kbps ~ 1Mbps	UVCAN/DroneCAN
	Sample-Point	50% or 87.5%	
	Available SERVO ID	1 ~ 254	1 ~ 127
	Available Node ID	1 ~ 2047	1 ~ 536870911
Connector Type	Input Signal Range	0 ~ 5V	1 ~ 127
	Position Sensor Type	Contactless Magnetic Encoder	
	Motor Type	Coreless	
	Amplifier / MCU	32bit programmable Digital	
	Operating Voltage Range	4.0V ~ 8.4V	
	Operating Voltage	At 4.8V	At 6.0V
	Operating Speed at no Load	261°/s (44RPM)	353°/s (59RPM)
	Stall Torque	21.0kgcm (206.0Ncm)	29.0kgcm (284.5Ncm)
	Peak Efficiency Torque	4.2kgcm (41.2Ncm)	5.8kgcm (56.9Ncm)
	Rest Current	30mA	30mA
Travel	Running Current at no Load	300mA	390mA
	Stall Current	3700mA	4800mA
	Deadband Width	4Step	4Step
	Travel / Command	90° / 4096	
	Servo mode	Left	Center
	Pos Command	+1366	+8192
	Pos [°]	-150	0
	Turn Mode	Left	Power On
	Pos Command	-16383	0
	Pos [°]	-359	0
Operational	Turn Range	-32760 ~ +32760 (CAN only)	+359
	Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
	Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)	
	Vibrations at no Load	MIL-STD-810G 514.6C-VII	
	Connector Wire Length	300mm	
	Connector Wire Gauge	20AWG	
	Connector Wire Strand Count	80/0.08	
	External Dimensions	40.0 x 20.0 x 38.0mm	
	Weight*	66.4g	
	Ball Bearing	Dual Ball Bearing	
Mechanical	Case Material	Engineering Plastic & Aluminum Heatsink	
	Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears	
	Gear Train Backlash	Max. 0.5°	
	Horn Gear Spline	H25T Ø6.0	
	Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)	
	IP-Rating	IP54	
	Revision	Rev. 1.1 / 03.01.2024	
	Changelog	-	
	*of the servo w/o horns and accessories		

MD85MG

#1-01656


**PERFORMANCE CHART****GENERAL SPECIFICATION**

MD85MG		
Control System	PWM / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	Cored Carbon Brush	
Ampfifier / MCU	32bit programmable Digital Amplifier with Mosfet Drive	
Operating Voltage Range	3.5V ~ 8.4V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	353°/s (59RPM)	462°/s (77RPM)
Stall Torque	3.6kgcm (35.3Ncm)	4.3kgcm (42.2Ncm)
Peak Efficiency Torque	0.7kgcm (6.9Ncm)	0.9kgcm (8.8Ncm)
Rest Current	30mA	30mA
Running Current at no Load	260mA	300mA
Stall Current	1300mA	1600mA
Deadband Width	2µs	2µs
Operating Travel	Default	±60°
	Programmable	Max. 320°
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	250mm	
Connector Wire Gauge	28AWG	
Connector Wire Strand Count	20/0.08	
External Dimensions	29.0 x 13.0 x 29.4mm	
Weight*	21.5g	
Ball Bearing	Single Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	5 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (M-I, M-X, M-O)	
IP-Rating	IP4X	
Revision	Rev. 1.1 / 03.01.2024	
Changelog	-	


*of the servo only w/o horns and accessories

MD250MW

#1-00707



1:1


PERFORMANCE CHART**GENERAL SPECIFICATION**

MD250MW			
Control System	PWM / TTL (Half Duplex)		
	Pulse Width 900µs 1500µs (Center) 2100µs		
Connector Type	Hitec 3P (JR 3P compatible)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Amplifier / MCU	32Bit programmable Digital with Mosfet Drive		
Operating Voltage Range	3.5V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	300°/s (50RPM)	375°/s (63RPM)	462°/s (77RPM)
Stall Torque	4.9kgcm (48.1Ncm)	6.1kgcm (59.8Ncm)	7.5kgcm (73.6Ncm)
Peak Efficiency Torque	1.0kgcm (9.8Ncm)	1.2kgcm (11.8Ncm)	1.5kgcm (14.7Ncm)
Rest Current	40mA	40mA	40mA
Running Current at no Load	110mA	150mA	190mA
Stall Current	1000mA	1300mA	1600mA
Deadband Width	2µs	2µs	2µs
Operating Travel	Default	±60°	
	Programmable	Max. 320°	
	Multi Turn/Continuous Rotation	n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	22AWG		
Connector Wire Strand Count	60/0.08		
External Dimensions	35.4 x 15.0 x 32.0mm		
Weight*	38.3g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Metal-Plastic & 4 Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (M-I25, R-ML25)		
IP-Rating	IP4X		
Revision	Rev. 1.1 / 03.01.2024		
Changelog	-		


*of the servo only w/o horns and accessories

MD261SW

#1-03052



1:1



PERFORMANCE CHART**GENERAL SPECIFICATION**

MD261SW			
Control System	PWM / TTL (Half Duplex)		
	Pulse Width 900µs 1500µs (Center) 2100µs		
Connector Type	Hitec 3P (JR 3P compatible)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	3.5V ~ 8.4V		
Operating Voltage	At 4.8V At 6.0V At 7.4V		
Operating Speed at no Load	200°/s (33RPM)	261°/s (44RPM)	316°/s (53RPM)
Stall Torque	6.5kgcm (63.7Ncm)	8.1kgcm (79.5Ncm)	10.0kgcm (98.1Ncm)
Peak Efficiency Torque	1.3kgcm (12.8Ncm)	1.6kgcm (15.7Ncm)	2.0kgcm (19.6Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	220mA	260mA	300mA
Stall Current	1400mA	1700mA	2100mA
Deadband Width	2µs	2µs	2µs
Operatings Travel	Default	±60°	
	Programmable	Max. 320°	
	Multi Turn/Continuous Rotation	n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	22AWG		
Connector Wire Strand Count	60/0.08		
External Dimensions	35.0 x 15.0 x 32.0mm		
Weight*	50.6g		
Ball Bearing	Dual Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	5 Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horn (M-125)		
IP-Rating	IP4X		
Revision	Rev. 1.0 / 05.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			


MD485HW

#1-01924

#1-02363 GP 30 Stück



1:1

PERFORMANCE CHART


7,4

GENERAL SPECIFICATION


MD485HW			
Control System	PWM / TTL (Half Duplex)		
	Pulse Width 900µs 1500µs (Center) 2100µs		
Connector Type	Hitec 3P (JR 3P compatible)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Amplifier / MCU	32bit Programmable Digital Mosfet Drive		
Operating Voltage Range	3.5V ~ 8.4V		
Operating Voltage	At 4.8V At 6.0V At 7.4V		
Operating Speed at no Load	300°/s (50RPM)	353°/s (59RPM)	400°/s (67RPM)
Stall Torque	4.8kgcm (47.1Ncm)	6.0kgcm (58.8Ncm)	7.4kgcm (72.6Ncm)
Peak Efficiency Torque	1.0kgcm (9.8Ncm)	1.2kgcm (11.8Ncm)	1.5kgcm (14.7Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	250mA	280mA	320mA
Stall Current	1000mA	1200mA	1500mA
Deadband Width	2µs	2µs	2µs
Operating Travel	Default	±60°	
	Programmable	Max. 320°	
	Multi Turn/Continuous Rotation	n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	24AWG		
Connector Wire Strand Count	40/0.08		
External Dimensions	39.8 x 19.8 x 38.0mm		
Weight*	43.3g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	4 Heavy Duty Resin Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)		
IP-Rating	IP4X		
Revision	Rev. 1.1 / 03.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

MD980TW

1-03166





1:1

**GENERAL SPECIFICATION**

MD980TW			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Coreless		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	4.8V	6.0V	7.4V
No Load Speed	0.28sec/60°	0.21sec/60°	0.17sec/60°
Stall Torque	26.0kgf-cm (361.07oz-in)	36.0kgf-cm (499.95oz-in)	44.0kgf-cm (611.05oz-in)
Peak Efficiency Torque	5.2kgf-cm (72.21oz-in)	7.2kgf-cm (99.99oz-in)	8.8kgf-cm (122.21oz-in)
Standing Current	30mA	30mA	30mA
No Load Running Current	300mA	390mA	500mA
Stall Current	4,200mA	4,800mA	6,200mA
Deadband	1µs	1µs	1µs
Operating Travel	Default: ±60°, Programmable: Max 320° / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	43.8mm x 22.4mm x 40.0mm (1.724inch x 0.882inch x 1.575inch)		
Weight	75.8g (2.674oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	25T(Ø6)		
IP-Rating	IP54		
Servo Amplifier Type	32bit programmable Digital		

MD146SH



1-03090

GENERAL SPECIFICATION

MD146SH			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.15sec/60°	0.13sec/60°
Stall Torque	-	5.9kgf·cm (81.94oz·in)	7.0kgf·cm (97.21oz·in)
Peak Efficiency Torque	-	1.2kgf·cm (16.39oz·in)	1.4kgf·cm (19.44oz·in)
Standing Current	-	30mA	30mA
No Load Running Current	-	250mA	300mA
Stall Current	-	2,100mA	2,600mA
Deadband	-	2μs	2μs
Operating Travel	Default: ±60°, Programmable: Max 320° / Pulse Width: 900~2100μs(Center:1500μs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	24AWG		
Dimensions	30.0mm x 10.0mm x 37.0mm (1.181inch x 0.394inch x 1.457inch)		
Weight	31.0g (1.093oz)		
Bearing Type	2 Ball Bearing		
Case Material	Aluminum Alloy		
Gear Material	1 Metal-Plastic & 4 Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	M25T(Ø5)		
IP-Rating	IP4X		
Servo Amplifier Type	32bit Programmable Digital		

MD70MH



1-03277

GENERAL SPECIFICATION

MD70MH			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Metal Brush		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.15sec/60°	0.12sec/60°
Stall Torque	-	3.1kgf·cm (43.05oz·in)	3.8kgf·cm (52.77oz·in)
Peak Efficiency Torque	-	0.6kgf·cm (8.33oz·in)	0.8kgf·cm (11.11oz·in)
Standing Current	-	30mA	30mA
No Load Running Current	-	200mA	240mA
Stall Current	-	1,000mA	1,300mA
Deadband	-	2μs	2μs
Operating Travel	Default: ±60°, Programmable: Max 320° / Pulse Width: 900~2100μs(Center:1500μs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	160mm (6.299inch)		
Connector Wire Gauge	28AWG		
Dimensions	23.6mm x 11.6mm x 30.0mm (0.929inch x 0.457inch x 1.181inch)		
Weight	13.0g (0.459oz)		
Bearing Type	1 Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Heavy Duty Resin & 4 Metal Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	M25T(Ø5)		
IP-Rating	IP4X		
Servo Amplifier Type	32bit programmable Digital		

MD845WP



1-03227

GENERAL SPECIFICATION

MD845WP			
Control System	PWM/TTL(Half Duplex)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	4.8V	6.0V	7.4V
No Load Speed	0.26sec/60°	0.21sec/60°	0.17sec/60°
Stall Torque	32.5kgf·cm (451.34oz·in)	40.5kgf·cm (562.44oz·in)	50.0kgf·cm (694.37oz·in)
Peak Efficiency Torque	6.5kgf·cm (90.27oz·in)	8.1kgf·cm (112.49oz·in)	10.0kgf·cm (138.87oz·in)
Standing Current	30mA	30mA	30mA
No Load Running Current	1,100mA	1,250mA	1,600mA
Stall Current	6,000mA	7,000mA	10,000mA
Deadband	2µs	2µs	2µs
Operating Travel	Default: ±60°, Programmable: Max 320° / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	20AWG		
Dimensions	66.0mm x 32.0mm x 62.1mm (2.598inch x 1.260inch x 2.445inch)		
Weight	228.9g (8.074oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic & Aluminum Heat Sink		
Gear Material	1 Metal-Plastic & 4 Steel Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	15T(Ø8)		
IP-Rating	IP67		
Servo Amplifier Type	32bit programmable Digital		

MD1100WP

#1-01638


**PERFORMANCE CHART****GENERAL SPECIFICATION**

MD1100WP		
Control System	PWM / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	5 Poles DC Cored Carbon Brush	
Amplifier / MCU	32bit programmable Digital with Mosfet Drive	
Operating Voltage Range	9.0V ~ 16.8V	
Operating Voltage	At 11.1V	At 14.8V
Operating Speed at no Load	231°/s (38RPM)	316°/s (53RPM)
Stall Torque	84.0kgcm (824.0Ncm)	110.0kgcm (1079.1Ncm)
Peak Efficiency Torque	16.8kgcm (164.8Ncm)	22.0kgcm (215.8Ncm)
Rest Current	90mA	90mA
Running Current at no Load	550mA	500mA
Stall Current	6500mA	8000mA
Deadband Width	2µs	2µs
Operating Travel	Default	±60°
	Programmable	Max. 320°
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	IEC-60068-2-64	
Connector Wire Length	270mm	
Connector Wire Gauge	18AWG (Signal: 20AWG)	
Connector Wire Strand Count	120/0.08 (80/0.08)	
External Dimensions	64.0 x 33.0 x 73.0mm	
Weight*	324.3g	
Ball Bearing	Dual Ball Bearing & Dual Needle Bearing	
Case Material	Rugged Aluminum Alloy	
Gear Material	1 Metal-Plastic & 3 Hardened Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	15T Ø8.0	
Accessories	Mounting Hardware, Servo Horn (I-MO)	
IP-Rating	IP67	
Revision	Rev. 1.1 / 03.01.2024	
Changelog	-	


*of the servo w/o only horns and accessories

MDR845WP

#1-01329




1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


MDR845WP			
Control System	PWM / TTL (Half Duplex)		
	Pulse Width 900µs 1500µs (Center) 2100µs		
Connector Type	Hitec 3P (JR 3P compatible)		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	4.0V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	231°/s (38RPM)	286°/s (48RPM)	353°/s (59RPM)
Stall Torque	32.5kgcm (318.8Ncm)	40.5kgcm (397.3Ncm)	50.0kgcm (490.5Ncm)
Peak Efficiency Torque	6.5kgcm (63.8Ncm)	8.1kgcm (79.5Ncm)	10.0kgcm (98.1Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	1100mA	1250mA	1600mA
Stall Current	6000mA	7000mA	10000mA
Deadband Width	2µs	2µs	2µs
Operating Travel	Default	±180°	
	Programmable	Max. ±8 Turns	
	Multi Turn/Continuous Rotation	Yes / Yes	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	66.0 x 32.0 x 62.1mm		
Weight*	229.4g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic & Aluminum Heatsink		
Gear Material	1 Metal-Plastic & 4 Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	15T Ø8.0		
Accessories	Mounting Hardware, Servo Horns (Q-MIA, Q-XA, Q-MIA)		
IP-Rating	IP67		
Revision	Rev. 1.1 / 04.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

MD245MW-RS485

#1-01677




1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


MD245MW-RS485			
Control System	RS485	Pulse Width -	
Connector Type	Hitec 4P		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Coreless		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	4.0V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	353°/s (59RPM)	462°/s (77RPM)	546°/s (91RPM)
Stall Torque	4.2kgcm (41.2Ncm)	5.2kgcm (51.0Ncm)	6.4kgcm (62.8Ncm)
Peak Efficiency Torque	0.9kgcm (8.8Ncm)	1.0kgcm (9.8Ncm)	1.3kgcm (12.8Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	110mA	150mA	190mA
Stall Current	1000mA	1300mA	1600mA
Deadband Width	n/a	n/a	n/a
Opearting Travel	Default Programmable Multi Turn/Continuous Rotation	±60° Max. 320° n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	22AWG		
Connector Wire Strand Count	60/0.08		
External Dimensions	32.4 x 16.8 x 32.8mm		
Weight*	35.2g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Metal-Plastic & 3 Metal Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horn (M-O25)		
IP-Rating	IP4X		
Revision	Rev. 1.0 / 05.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

MD250MW-RS485

#1-01676





1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**

MD250MW-RS485			
Control System	RS485	Pulse Width -	
Connector Type	Hitec 4P		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Cored Carbon Brush		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	4.0V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	300°/s (50RPM)	375°/s (63RPM)	462°/s (77RPM)
Stall Torque	4.9kgcm (48.1Ncm)	6.1kgcm (59.8Ncm)	7.5kgcm (73.6Ncm)
Peak Efficiency Torque	1.0kgcm (9.8Ncm)	1.2kgcm (11.8Ncm)	1.5kgcm (14.7Ncm)
Rest Current	40mA	40mA	40mA
Running Current at no Load	110mA	150mA	190mA
Stall Current	1000mA	1300mA	1600mA
Deadband Width	n/a	n/a	n/a
Operatings Travel	Default	±60°	
	Programmable	Max. 320°	
	Multi Turn/Continuous Rotation	n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	22AWG		
Connector Wire Strand Count	60/0.08		
External Dimensions	35.4 x 15.0 x 32.0mm		
Weight*	40.0g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Metal-Plastic & 4 Steel Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horn (M-125)		
IP-Rating	IP4X		
Revision	Rev. 1.0 / 05.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

MD950TW-RS485


#1-01675

**PERFORMANCE CHART****GENERAL SPECIFICATION**


MD950TW-RS485			
Control System	RS485	Pulse Width	-
Connector Type	Hitec 4P		
Position Sensor Type	Contactless Magnetic Encoder		
Motor Type	Coreless		
Amplifier / MCU	32bit programmable Digital		
Operating Voltage Range	4.0V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	261°/s (44RPM)	353°/s (59RPM)	429°/s (71RPM)
Stall Torque	21.0kgcm (206.0Ncm)	29.0kgcm (284.5Ncm)	35.0kgcm (343.4Ncm)
Peak Efficiency Torque	4.2kgcm (41.2Ncm)	5.8kgcm (56.9Ncm)	7.0kgcm (68.7Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	300mA	390mA	500mA
Stall Current	3700mA	4800mA	6200mA
Deadband Width	n/a	n/a	n/a
Operarting Travel	Default	±60°	
	Programmable	Max. 320°	
	Multi Turn/Continuous Rotation	n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	40.0 x 20.0 x 38.0mm		
Weight*	66.3g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering plastic & Aluminum Heatsink		
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)		
IP-Rating	IP54		
Revision	Rev. 1.0 / 05.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

MD980TW-RS485

#1-03230



PERFORMANCE CHART





GENERAL SPECIFICATION

MD980TW-RS485			
Control System	RS485		
Connector Type	Pulse Width -		
Position Sensor Type	Hitec 4P		
Motor Type	Contactless Magnetic Encoder		
Amplifier / MCU	Coreless		
Operating Voltage Range	32bit programmable Digital		
Operating Voltage	4.0V ~ 8.4V		
Operating Speed at no Load	At 4.8V	At 6.0V	At 7.4V
Stall Torque	214°/s (36RPM)	286°/s (48RPM)	353°/s (59RPM)
Peak Efficiency Torque	26.0kgcm (255.1Ncm)	36.0kgcm (353.2Ncm)	44.0kgcm (431.6Ncm)
Rest Current	5.2kgcm (51.0Ncm)	7.2kgcm (70.6Ncm)	8.8kgcm (86.3Ncm)
Running Current at no Load	30mA	30mA	30mA
Stall Current	300mA	390mA	500mA
Deadband Width	4200mA	4800mA	6200mA
Opearting Travel	n/a	n/a	n/a
Default	±60°		
Programmable	Max. 320°		
Multi Turn/Continuous Rotation	n/a / n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	43.8 x 22.4 x 40.0mm		
Weight*	76.7g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering plastic		
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25, HD-IL25, HD-LL25, HD-IG25, HD-LG25)		
IP-Rating	IP54		
Revision	Rev. 1.0 / 08.01.2024		
Changelog	-		
*of the servo only w/o horns and accessories			

D485HW

#1-00066

#1-02362 GP 30 Stück

**PERFORMANCE CHART****GENERAL SPECIFICATION**



D485HW			
Control System	PWM / TTL (Half Duplex)		
	Pulse Width 900µs 1500µs (Center) 2100µs		
Connector Type	Hitec 3P (JR 3P compatible)		
Position Sensor Type	Indirect Drive / 1M Cycle Long Life		
Motor Type	Cored Metal Brush		
Amplifier / MCU	32bit programmable Digital with Mosfet Drive		
Operating Voltage Range	3.5V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	300°/s (50RPM)	353°/s (59RPM)	400°/s (67RPM)
Stall Torque	5.2kgcm (51.0Ncm)	6.4kgcm (62.8Ncm)	7.5kgcm (73.6Ncm)
Peak Efficiency Torque	1.0kgcm (9.8Ncm)	1.3kgcm (12.8Ncm)	1.5kgcm (14.7Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	250mA	280mA	320mA
Stall Current	1000mA	1200mA	1500mA
Deadband Width	2µs	2µs	2µs
Operating Travel	Default Programmable Multi Turn/Continuous Rotation	±60° Max. 175° n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	24AWG		
Connector Wire Strand Count	40/0.08		
External Dimensions	39.8 x 19.8 x 38.0mm		
Weight*	45.0g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	4 Heavy Duty Resin Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)		
IP-Rating	IP54		
Revision	Rev. 1.1 / 04.01.2024		
Changelog	-		

*of the servo only w/o horns and accessories

D646WP

#1-00072

#1-02354 GP 24 Stück


**PERFORMANCE CHART****GENERAL SPECIFICATION**

D646WP		
Control System	PWM / TTL (Half Duplex)	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contact Analog / 4 Slider / 1M Cycle Long Life	
Motor Type	Cored Carbon Brush	
Amplifier / MCU	32bit programmable Digital with Mosfet Drive	
Operating Voltage Range	3.5V ~ 8.4V	
Operating Voltage	At 4.8V At 6.0V At 7.4V	
Operating Speed at no Load	250°/s (42RPM)	316°/s (33RPM)
Stall Torque	7.5kgcm (73.6Ncm)	9.6kgcm (94.2Ncm)
Peak Efficiency Torque	1.5kgcm (14.7Ncm)	1.9kgcm (18.6Ncm)
Rest Current	30mA	30mA
Running Current at no Load	270mA	300mA
Stall Current	1500mA	1800mA
Deadband Width	2µs	2µs
Operating Travel	Default	±60°
	Programmable	Max. 170°
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	22AWG	
Connector Wire Strand Count	60/0.08	
External Dimensions	41.8 x 21.0 x 40.1mm	
Weight*	61.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)	
IP-Rating	IP67	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	


*of the servo only w/o horns and accessories

D954SW

#116954



1:1



PERFORMANCE CHART**GENERAL SPECIFICATION**

D954SW						
Control System	PWM / TTL (Half Duplex) Pulses Width 900µs 1500µs (Center) 2100µs					
Connector Type	Hitec 3P (JR 3P compatible)					
Position Sensor Type	Indirect Drive / 1M Cycle Long Life					
Motor Type	Coreless					
Amplifier / MCU	32bit programmable Digital with Mosfet Drive					
Operating Voltage Range	3.5V ~ 8.4V					
Operating Voltage	At 4.8V	At 6.0V	At 7.4V			
Operating Speed at no Load	316°/s (53RPM)	400°/s (67RPM)	500°/s (83RPM)			
Stall Torque	16.0kgcm (157.0Ncm)	24.0kgcm (235.4Ncm)	29.0kgcm (284.5Ncm)			
Peak Efficiency Torque	3.6kgcm (35.3Ncm)	4.8kgcm (47.1Ncm)	5.8kgcm (56.9Ncm)			
Rest Current	30mA	30mA	30mA			
Running Current at no Load	300mA	400mA	500mA			
Stall Current	3200mA	4200mA	5200mA			
Deadband Width	1µs	1µs	1µs			
Operating Travel	Default Programmable Multi Turn/Continuous Rotation	±60° ** Max. 175° n/a / n/a				
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)					
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)					
Vibrations at no Load	-					
Connector Wire Length	300mm					
Connector Wire Gauge	20AWG					
Connector Wire Strand Count	80/0.08					
External Dimensions	40.0 x 20.0 x 37.0mm					
Weight*	66.0g					
Ball Bearing	Dual Ball Bearing					
Case Material	Engineering Plastic & Aluminum Heatsink					
Gear Material	1 Metal-Plastic & 3 Steel Gears					
Gear Train Backlash	Max. 0.5°					
Horn Gear Spline	H25T Ø6.0					
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25)					
IP-Rating	IP54					
Revision	Rev. 1.1 / 04.01.2024					
Changelog	-					
*of the servo only w/o horns and accessories						
** also available with 270°						

D951TW

#116951


#1-02359 GP 24 Stück

**PERFORMANCE CHART****GENERAL SPECIFICATION**


D951TW		
Control System	PWM / TTL (Half Duplex)	
	PWM Range 900µs 1500µs 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 1M Cycle Long Life	
Motor Type	Coreless	
Amplifier / MCU	32bit programmable Digital with Mosfet Drive	
Operating Voltage Range	3.5V ~ 8.4V	
Operating Voltage	At 4.8V At 6.0V At 7.4V	
Operating Speed at no Load	261°/s (44RPM)	353°/s (59RPM)
Stall Torque	21.0kgcm (206.0Ncm)	29.0kgcm (284.5Ncm)
Peak Efficiency Torque	4.2kgcm (41.2Ncm)	5.8kgcm (56.9Ncm)
Rest Current	30mA	30mA
Running Current at no Load	300mA	390mA
Stall Current	3700mA	4800mA
Deadband Width	1µs	1µs
	Default ±60°	
Operating Travel	Programmable Max. 175°	
	Multi Turn/Continuous Rotation n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20.0 x 38.0mm	
Weight*	80.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Aluminum Alloy	
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Mounting Hardware, HD-IM25, HD-LS25, HD-OS25, HD-X25	
IP-Rating	IP54	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	
*of the servo only w/o horns and accessories		

D980TW

#1-02982



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


D980TW			
Control System	PWM / TTL (Half Duplex)		
	Pulse Width 900µs 1500µs (Center) 2100µs		
Connector Type	Hitec 3P (JR 3P compatible)		
Position Sensor Type	Indirect Drive / 4 Slider / 1M Cycle Long Life		
Motor Type	Coreless		
Amplifier / MCU	32bit programmable Digital with Mosfet Drive		
Operating Voltage Range	3.5V ~ 8.4V		
Operating Voltage	At 4.8V	At 6.0V	At 7.4V
Operating Speed at no Load	214°/s (36RPM)	286°/s (48RPM)	343°/s (59RPM)
Stall Torque	26.0kgcm (255.1Ncm)	36.0kgcm (353.2Ncm)	44.0kgcm (431.6Ncm)
Peak Efficiency Torque	5.5kgcm (54.0Ncm)	7.2kgcm (70.6Ncm)	8.8kgcm (86.3Ncm)
Rest Current	30mA	30mA	30mA
Running Current at no Load	300mA	390mA	500mA
Stall Current	4200mA	4800mA	6200mA
Deadband Width	1µs	1µs	1µs
Operatings Travel	Default	±60°	
	Programmable	Max. 175°	
	Multi Turn/Continuous Rotation	n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)		
Vibrations at no Load	-		
Connector Wire Length	300mm		
Connector Wire Gauge	20AWG		
Connector Wire Strand Count	80/0.08		
External Dimensions	43.8 x 22.4 x 40.0mm		
Weight*	78.2g		
Ball Bearing	Dual Ball Bearing		
Case Material	Engineering Plastic & Aluminum Heatsink		
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears		
Gear Train Backlash	Max. 0.5°		
Horn Gear Spline	H25T Ø6.0		
Accessories	Mounting Hardware, Servo Horns (HD-IM25, HD-LS25, HD-OS25, HD-X25, HD-IL25, HD-LL25, HD-IG25, HD-LG25)		
IP-Rating	IP54		
Revision	Rev. 1.1 / 04.01.2024		
Changelog	-		

*of the servo only w/o horns and accessories


HS-53

#112053

#112054 GP 20 Stück



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


HS-53		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Direct Drive / 2 Slider	
Motor Type	Cored Metal Brush	
Amplifier / MCU	Analog	
Operating Voltage Range	4.8V ~ 6.0V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	429°/s (71RPM)	546°/s (91RPM)
Stall Torque	1.5kgcm (14.7Ncm)	1.9kgcm (18.6Ncm)
Peak Efficiency Torque	0.3kgcm (2.9Ncm)	0.4kgcm (3.9Ncm)
Rest Current	8mA	10mA
Running Current at no Load	200mA	250mA
Stall Current	440mA	550mA
Deadband Width	5µs	5µs
Operating Travel	Default	±60°
	Programmable	n/a
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	250mm	
Connector Wire Gauge	28AWG	
Connector Wire Strand Count	20/0.08	
External Dimensions	22.8 x 11.4 x 24.5mm	
Weight*	8.0g	
Ball Bearing	n/a	
Case Material	Engineering Plastic	
Gear Material	5 Resin Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	15T Ø4.0	
Accessories	Tapping Screw, Servo Horns (FS-IL, FS-X)	
IP-Rating	IP4X	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories


HS-81

#112081

#112084 GP 20 Stück



1:2

PERFORMANCE CHART**GENERAL SPECIFICATION**


HS-81		
Control System	Pulse Width Modulation (PWM)	
	PWM Range '900µs 1500µs 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Direct Drive	
Motor Type	Cored / 3 poles Ferrite Motor	
Amplifier / MCU	Analog	
Operating Voltage Range	4.8V ~ 6.0V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	546°/s (91RPM)	667°/s (111RPM)
Stall Torque	2.6kgcm (25.5Ncm)	3.0kgcm (29.4Ncm)
Peak Efficiency Torque	0.5kgcm (4.9Ncm)	0.6kgcm (5.9Ncm)
Rest Current	9mA	9mA
Running Current at no Load	220mA	280mA
Stall Current	-	-
Deadband Width	5µs	5µs
Operating Travel	Default	±60°
	Programmable	n/a
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	250mm	
Connector Wire Gauge	28AWG	
Connector Wire Strand Count	20/0.08	
External Dimensions	29.8 x 12.0 x 26.0mm	
Weight*	16.6g	
Ball Bearing	n/a	
Case Material	Engineering Plastic	
Gear Material	3 resin & 1 Heavy Duty Resin Gears	
Gear Train Backlash	n/a	
Horn Gear Spline	24T Ø5.76	
Accessories	Mounting Hardware, Servo Horns (M-I, M-X, M-O)	
IP-Rating	IP4X	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories


HS-85MG

#112086

#112091 GP 20 Stück



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**



HS-85MG		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Cored / 3 Pole Ferrite Motor	
Amplifier / MCU	Analog	
Operating Voltage Range	4.8V ~ 6.0V	
Operating Voltage	At 4.8V At 6.0V	
Operating Speed at no Load	375°/s (63RPM) 429°/s (71RPM)	
Stall Torque	3.0kgcm (29.4Ncm) 3.5kgcm (34.3Ncm)	
Peak Efficiency Torque	0.6kgcm (5.9Ncm) 0.7kgcm (6.9Ncm)	
Rest Current	8mA 8mA	
Running Current at no Load	240mA 240mA	
Stall Current	- -	
Deadband Width	5µs 5µs	
Operating Travel	Default ±60°	
	Programmable n/a	
	Multi Turn/Continuous Rotation n/a / n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	250mm	
Connector Wire Gauge	28AWG	
Connector Wire Strand Count	20/0.08	
External Dimensions	29.0 x 13.0 x 29.4mm	
Weight*	21.9g	
Ball Bearing	Single Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Resin & 4 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (M-I, M-X, M-O)	
IP-Rating	IP4X	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories

HS-311

#112311

#IND-112314 GP 30 Stück

**PERFORMANCE CHART****GENERAL SPECIFICATION**


HS-311	
Control System	PWM Pulse Width 900µs 1500µs (Center) 2100µs
Connector Type	Hitec 3P (JR 3P compatible)
Position Sensor Type	Direct Drive / 4 Slider
Motor Type	Cored Metal Brush
Amplifier / MCU	Analog
Operating Voltage Range	4.8V ~ 6.0V
Operating Voltage	At 4.8V At 6.0V
Operating Speed at no Load	316°/s (53RPM) 400°/s (67RPM)
Stall Torque	3.0kgcm (29.4Ncm) 3.7kgcm (36.3Ncm)
Peak Efficiency Torque	0.6kgcm (5.9Ncm) 0.7kgcm (6.9Ncm)
Rest Current	7mA 8mA
Running Current at no Load	160mA 180mA
Stall Current	700mA 800mA
Deadband Width	5µs 5µs
Operating Travel	Default ±60° Programmable n/a Multi Turn/Continuous Rotation n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)
Vibrations at no Load	-
Connector Wire Length	300mm
Connector Wire Gauge	24AWG
Connector Wire Strand Count	40/0.08
External Dimensions	40.0 x 20.0 x 36.5mm
Weight*	43.0g
Ball Bearing	Single Resin Bushing
Case Material	Engineering Plastic
Gear Material	4 Resin Gears
Gear Train Backlash	Max. 0.5°
Horn Gear Spline	24T Ø6.0
Accessories	Mounting Hardware, Servo Horns (R-O, R-X, R-I, R-D, R-C, R-XA)
IP-Rating	IP4X
Revision	Rev. 1.1 / 04.01.2024
Changelog	-

*of the servo only w/o horns and accessories


HS-322HD

#112322

#112326 GP 30 Stück



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


HS-322HD	
Control System	PWM Pulse Width 900µs 1500µs (Center) 2100µs
Connector Type	Hitec 3P (JR 3P compatible)
Position Sensor Type	Direct Drive / 4 Slider
Motor Type	Cored Metal Brush
Amplifier / MCU	Analog
Operating Voltage Range	4.8V ~ 6.0V
Operating Voltage	At 4.8V At 6.0V
Operating Speed at no Load	316°/s (53RPM) 400°/s (67RPM)
Stall Torque	3.0kgcm (29.4Ncm) 3.7kgcm (36.3Ncm)
Peak Efficiency Torque	0.6kgcm (5.9Ncm) 0.7kgcm (6.9Ncm)
Rest Current	7mA 8mA
Running Current at no Load	160mA 180mA
Stall Current	700mA 800mA
Deadband Width	5µs 5µs
Operating Travel	Default ±60° Programmable n/a Multi Turn/Continuous Rotation n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)
Vibrations at no Load	-
Connector Wire Length	300mm
Connector Wire Gauge	24AWG
Connector Wire Strand Count	40/0.08
External Dimensions	40.0 x 20.0 x 36.5mm
Weight*	43.0g
Ball Bearing	Dual Resin Bushing
Case Material	Engineering Plastic
Gear Material	2 Resin & 2 Heavy Duty Resin Gears
Gear Train Backlash	Max. 0.5°
Horn Gear Spline	24T Ø6.0
Accessories	Mounting Hardware, Servo Horns (R-O, R-X, R-I, R-D, R-C)
IP-Rating	IP4X
Revision	Rev. 1.1 / 04.01.2024
Changelog	-

*of the servo only w/o horns and accessories


HS-325HB

#112325

#1-02361 GP 30 Stück



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**



HS-325HB		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Direct Drive / 4 Slider	
Motor Type	Cored Metal Brush	
Amplifier / MCU	Analog	
Operating Voltage Range	4.8V ~ 6.0V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	316°/s (53RPM)	400°/s (67RPM)
Stall Torque	3.0kgcm (29.4Ncm)	3.7kgcm (36.3Ncm)
Peak Efficiency Torque	0.6kgcm (5.9Ncm)	0.7kgcm (6.9Ncm)
Rest Current	7mA	8mA
Running Current at no Load	160mA	180mA
Stall Current	700mA	800mA
Deadband Width	5µs	5µs
Operating Travel	Default	±60°
	Programmable	n/a
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	24AWG	
Connector Wire Strand Count	40/0.08	
External Dimensions	40.0 x 20.0 x 36.5mm	
Weight*	43.0g	
Ball Bearing	Dual Resin Bushing	
Case Material	Engineering Plastic	
Gear Material	2 Resin & 2 Heavy Duty Resin Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (R-O, R-X, R-I, R-D, R-C)	
IP-Rating	IP4X	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories

HS-645MG

#112645

#112648 GP 30 Stück

**PERFORMANCE CHART****GENERAL SPECIFICATION**


HS-645MG		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Cored Metal Brush	
Amplifier / MCU	Analog	
Operating Voltage Range	4.8V ~ 6.0V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	250°/s (42RPM)	300°/s (50RPM)
Stall Torque	7.7kgcm (75.5Ncm)	9.6kgcm (94.2Ncm)
Peak Efficiency Torque	1.5kgcm (14.7Ncm)	1.9kgcm (18.6Ncm)
Rest Current	9mA	9mA
Running Current at no Load	350mA	450mA
Stall Current	-	-
Deadband Width	8µs	8µs
Operating Travel	Default	±60°
	Programmable	n/a
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-31°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	22AWG	
Connector Wire Strand Count	60/0.08	
External Dimensions	40.6 x 19.6 x 37.8mm	
Weight*	55.2g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic Gear & 3 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T / Ø6.0	
Accessories	Mounting Hardware, Servo Horns (R-O, R-XA, HD-IS, HD-LS, HD-OS)	
IP-Rating	IP4X	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories


HS-646WP

#115646

#1-02352 GP 24 Stück



1:1



PERFORMANCE CHART**GENERAL SPECIFICATION**

HS-646WP		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 4 Slider / 1M cycle Long Life	
Motor Type	Cored Carbon Brush / 3 Pole Ferrite Motor	
Amplifier / MCU	Analog	
Operating Voltage Range	6.0V ~ 7.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	300°/s (50RPM)	353°/s (59RPM)
Stall Torque	9.6kgcm (94.2Ncm)	11.6kgcm (113.8Ncm)
Peak Efficiency Torque	1.9kgcm (18.6Ncm)	2.3kgcm (22.6Ncm)
Rest Current	8mA	8mA
Running Current at no Load	400mA	600mA
Stall Current	2000mA	2200mA
Deadband Width	4µs	4µs
Operating Travel	Default	±60°
	Programmable	n/a
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	22AWG	
Connector Wire Strand Count	60/0.08	
External Dimensions	41.8 x 21.0 x 40.0mm	
Weight*	61.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories	Mounting Hardware, Servo Horns (R-O, R-XA, HD-IS, HD-LS, HD-OS)	
IP-Rating	IP67	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories

HS-1005SGT

#138105


GENERAL SPECIFICATION**PERFORMANCE CHART**

HS-1005SGT	
Control System	PWM Pulse Width 900µs 1500µs (Center) 2100µs
Connector Type	Hitec 3P (JR 3P compatible)
Position Sensor Type	Indirect Drive / 1M Cycle Long Life
Motor Type	Cored Carbon Brush
Amplifier / MCU	Digital with Mosfet Drive
Operating Voltage Range	9.0V ~ 16.8V (Signal: 3.5V ~ 8.4V)
Operating Voltage	At 11.1V At 14.8V
Operating Speed at no Load	231°/s (38RPM) 316°/s (53RPM)
Stall Torque	84.0kgcm (824.0Ncm) 110.0kgcm (1079.1Ncm)
Peak Efficiency Torque	16.8kgcm (164.8Ncm) 22.0kgcm (215.8Ncm)
Rest Current	90mA 130mA
Running Current at no Load	1100mA 1300mA
Stall Current	5500mA 6500mA
Deadband Width	2µs 2µs
Operating Travel	Default ±60° Programmable n/a Multi Turn/Continuous Rotation n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)
Vibrations at no Load	IEC-60068-2-64
Connector Wire Length	250mm
Connector Wire Gauge	18AWG (Signal: 20AWG)
Connector Wire Strand Count	120/0.08 (80/0.08)
External Dimensions	64.0 x 33.0 x 73.0mm
Weight*	310.0g
Ball Bearing	Dual Ball Bearing
Case Material	Aluminum Alloy
Gear Material	1 Metal-Plastic & 3 Steel Gears
Gear Train Backlash	Max. 0.5°
Horn Gear Spline	15T Ø8.0
Accessories	Mounting Hardware, Servo Horn (I-MO)
IP-Rating	IP54
Revision	Rev. 1.1 / 04.01.2024
Changelog	-


*of the servo only w/o horns and accessories

HS-1100WP

#138100



1:2

PERFORMANCE CHART**GENERAL SPECIFICATION**


General Specification		HS-1100WP
Control System	PWM	Pulse Width 900µs 1500µs (Center) 2100µs
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 1M Cycle Long Life	
Motor Type	5 Poles DC Cored Carbon Brush	Digital with Mosfet Drive
Amplifier / MCU		9.0V ~ 16.8V (Signal: 3.5V ~ 8.4V)
Operating Voltage Range		At 11.1V At 14.8V
Operating Voltage		231°/s (38RPM) 316°/s (53RPM)
Operating Speed at no Load		84.0kgcm (824.0Ncm) 110.0kgcm (1079.1Ncm)
Stall Torque		16.8kgcm (164.8Ncm) 22.0kgcm (215.8Ncm)
Peak Efficiency Torque		90mA 130mA
Rest Current		1100mA 1300mA
Running Current at no Load		5500mA 6500mA
Stall Current		2µs 2µs
Deadband Width		Default ±60°
Operating Travel	Programmable	n/a
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	250mm	
Connector Wire Gauge	18AWG (Signal: 20AWG)	
Connector Wire Strand Count	120/0.08 (80/0.08)	
External Dimensions	64.0 x 33.0 x 73.0mm	
Weight*	320.0g	
Ball Bearing	Dual Ball Bearing & Dual Needle Bearing	
Case Material	Aluminum Alloy	
Gear Material	1 Metal-Plastic & 3 Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	15T Ø8.0	
Accessories	Mounting Hardware, Servo Horn (I-MO)	
IP-Rating	IP67	
Revision	Rev. 1.1 / 04.01.2024	
Changelog	-	

*of the servo only w/o horns and accessories

HS-5125MG


#113125

#1-03035 GP 15 Stück



1:1

PERFORMANCE CHART




GENERAL SPECIFICATION

HS-5125MG		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Cored Metal Brush	
Amplifier / MCU	8bit programmable Digital	
Operating Voltage Range	3.5V ~ 8.4V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	333°/s (56RPM)	429°/s (71RPM)
Stall Torque	2.8kgcm (27.5Ncm)	3.3kgcm (32.4Ncm)
Peak Efficiency Torque	0.6kgcm (5.9Ncm)	0.7kgcm (6.9Ncm)
Rest Current	3mA	3mA
Running Current at no Load	180mA	230mA
Stall Current	1100mA	1400mA
Deadband Width	2µs	2µs
Operating Travel	Default	±60°
	Programmable	Max. 175°
	Multi Turn/Continuous Rotation	n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	22AWG	
Connector Wire Strand Count	60/0.08	
External Dimensions	30.0 x 10.0 x 34.0mm	
Weight*	24.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 4 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	25T Ø5.0	
Accessories	Mounting Hardware, Servo Horns (MS-L25, MS-ML25)	
IP-Rating	IP4X	
Revision	Rev. 1.0 / 08.01.2024	
Changelog	-	


*of the servo only w/o horns and accessories

HS-5245MG

#113245



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**



HS-5245MG		
Control System	PWM	Pulse Width: 900~2100μs(Center:1500μs)
Connector Type		
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Cored Metal Brush	
Amplifier / MCU	8bit programmable Digital	
Operating Voltage Range**	3.5V ~ 8.4V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	0.15sec/60°	0.12sec/60°
Stall Torque	4.4kgf·cm (61.1 oz-in)	5.5kgf·cm (76.4 oz-in)
Peak Efficiency Torque	0.9kgf·cm (12.5 oz-in)	1.1kgf·cm (15.3 oz-in)
Rest Current	3mA	3mA
Running Current at no Load	260mA	360mA
Stall Current	1,600mA	2,000mA
Deadband Width	2μs	2μs
Operating Travel	Default	±60°
	Programmable	Max. 175°
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	22AWG	
Connector Wire Strand Count		
External Dimensions	32.2mm x 16.8mm x 31.0mm	
Weight*	32.0g	
Ball Bearing	2 Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories		
IP-Rating	IP4X	
Revision		
Changelog		

*of the servo only w/o horns and accessories

**At the Max voltage, it is recommended to be used only for a short time duration.

HS-5565MG

#114565

**PERFORMANCE CHART****GENERAL SPECIFICATION**


HS-5565MG		
Control System	PWM	
	Pulse Width: 900~2100μs(Center:1500μs)	
Connector Type		
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Cored Metal Brush	
Amplifier / MCU	8bit programmable Digital	
Operating Voltage Range**	3.5V ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	0.11sec/60°	0.09sec/60°
Stall Torque	11.0kgf-cm (152.8 oz-in)	14.0kgf-cm (194.4 oz-in)
Peak Efficiency Torque	2.2kgf-cm (30.6 oz-in)	2.8kgf-cm (38.9 oz-in)
Rest Current	4mA	4mA
Running Current at no Load	260mA	300mA
Stall Current	2,100mA	2,700mA
Deadband Width	2μs	2μs
Operating Travel	Default	±60°
	Programmable	Max. 175°
	Continuous Rotation	n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm (11.811inch)	
Connector Wire Gauge	24AWG	
Connector Wire Strand Count		
External Dimensions	40.0mm x 20.0mm x 38.0mm	
Weight*	59.0g	
Ball Bearing	2 Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Metal Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories		
IP-Rating	IP54	
Revision		
Changelog		

*of the servo only w/o horns and accessories


**At the Max voltage, it is recommended to be used only for a short time duration.

HS-7955TG

#113957



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


HS-7955TG		
Control System	PWM	
	Pulse Width: 900~2100μs(Center:1500μs)	
Connector Type		
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Coreless	
Amplifier / MCU	8bit programmable Digital	
Operating Voltage Range**	3.5V ~ 8.4V	
Operating Voltage	At 4.8V	At 6.0V
Operating Speed at no Load	0.19sec/60°	0.15sec/60°
Stall Torque	18.0kgf·cm (250.0 oz-in)	24.0kgf·cm (333.3 oz-in)
Peak Efficiency Torque	3.6kgf·cm (50.0 oz-in)	4.8kgf·cm (66.7 oz-in)
Rest Current	9mA	9mA
Running Current at no Load	220mA	300mA
Stall Current	3,400mA	4,200mA
Deadband Width	1μs	1μs
Operating Travel	Default	±60°
	Programmable	Max. 175°
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	22AWG	
Connector Wire Strand Count		
External Dimensions	40.0mm x 20.0mm x 37.0mm	
Weight*	65.0g	
Ball Bearing	2 Ball Bearing	
Case Material	Engineering Plastic & Aluminum Heat Sink	
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	24T Ø6.0	
Accessories		
IP-Rating		
Revision		
Changelog		

*of the servo only w/o horns and accessories


**At the Max voltage, it is recommended to be used only for a short time duration.

HS-M7990TH

#114990



1:1

PERFORMANCE CHART**GENERAL SPECIFICATION**


HS-M7990TH		
Control System	PWM	
	Pulse Width: 900~2100μs(Center:1500μs)	
Connector Type		
Position Sensor Type	Contactless Magnetic Encoder	
Motor Type	Coreless	
Amplifier / MCU	8bit programmable Digital	
Operating Voltage Range**	3.5V ~ 8.4V	
Operating Voltage	At 6.V	At 7.4V
Operating Speed at no Load	0.21sec/60°	0.17sec/60°
Stall Torque	36.0kgf·cm (499.9 oz-in)	44.0kgf·cm (611.0 oz-in)
Peak Efficiency Torque	7.2kgf·cm (100.0 oz-in)	8.8kgf·cm (122.2 oz-in)
Rest Current	22mA	23mA
Running Current at no Load	400mA	480mA
Stall Current	8,100mA	9,900mA
Deadband Width	2μs	2μs
Operating Travel	Default	±60°
	Programmable	Max 300°
	Continuous Rotation	n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Vibrations at no Load	-	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count		
External Dimensions	43.8mm x 22.4mm x 40.0mm	
Weight*	79.0g	
Ball Bearing	2 Ball Bearing	
Case Material	Engineering Plastic & Aluminum Heat Sink	
Gear Material	1 Metal-Plastic & 3 Titanium Alloy Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	25T Ø6.0	
Accessories		
IP-Rating	IP54	
Revision		
Changelog		

*of the servo only w/o horns and accessories


**At the Max voltage, it is recommended to be used only for a short time duration.

HSB-9485SH-270°

#1-00409



1:1



PERFORMANCE CHART**GENERAL SPECIFICATION**

HSB-9485SH-270°		
Control System	PWM	
	Pulse Width 900µs 1500µs (Center) 2100µs	
Connector Type	Hitec 3P (JR 3P compatible)	
Position Sensor Type	Indirect Drive / 4 Slider / 1M Cycle Long Life	
Motor Type	BLDC	
Amplifier / MCU	16bit programmable Digital Amplifier with Mosfet Drive	
Operating Voltage Range	4.0V ~ 8.4V	
Operating Voltage	At 6.0V	At 7.4V
Operating Speed at no Load	333°/s (56RPM)	400°/s (67RPM)
Stall Torque	26.0kgcm (255.1Ncm)	26.0kgcm (255.1Ncm)
Peak Efficiency Torque	5.2kgcm (51.0Ncm)	5.2kgcm (51.0Ncm)
Rest Current	30mA	30mA
Running Current at no Load	360mA	430mA
Stall Current	1100mA	900mA
Deadband Width	1µs	1µs
Operating Travel	Default Programmable Multi Turn/Continuous Rotation	±60° Max. 270° n/a / n/a
Operating Temperature Range	-20°C ~ +60°C (-4°F ~ +140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~ +176°F)	
Connector Wire Length	300mm	
Connector Wire Gauge	20AWG	
Connector Wire Strand Count	80/0.08	
External Dimensions	40.0 x 20,0 x 37.7mm	
Weight*	62.0g	
Ball Bearing	Dual Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	1 Metal-Plastic & 3 Steel Gears	
Gear Train Backlash	Max. 0.5°	
Horn Gear Spline	H25T Ø6.0	
Accessories	Servo Horn (HD-LS25)	
IP-Rating	IP54	
Revision	Rev. 1.0 / 09.01.2024	
Changelog	-	

*of the servo w/o horns and accessories

HS-425BB



1-03235

GENERAL SPECIFICATION

HS-425BB		
Control System	PWM	
Position Sensor Type	Contact Analog Potentiometer	
Motor Type	Cored Metal Brush	
Operating Voltage Range	4.8 ~ 6.0V	
Voltage	4.8V	6.0V
No Load Speed	0.21sec/60°	0.16sec/60°
Stall Torque	3.1kgf·cm (43.0oz-in)	3.9kgf·cm (54.16oz-in)
Peak Efficiency Torque	0.6kgf·cm (8.3 oz-in)	0.8kgf·cm (11.1 oz-in)
Standing Current	8mA	8mA
No Load Running Current	150mA	180mA
Stall Current	600mA	750mA
Deadband	5µs	5µs
Operating Travel	Default: ±60°, Non-programmable / Pulse Width: 900~2100µs(Center:1500µs)	
Continuous Rotation	n/a	
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)	
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)	
Connector Wire Length	300mm (11.811inch)	
Connector Wire Gauge	24WAG	
Dimensions	40.6mm x 19.8mm x 36.6mm (1.598inch x 0.780inch x 1.441inch)	
Weight	46.0g (1.623oz)	
Bearing Type	2 Ball Bearing	
Case Material	Engineering Plastic	
Gear Material	4 Resin Gears	
Gear Train Backlash	Max 0.5°	
Horn Gear Spline	24T(Ø6)	
IP-Rating	IP4X	
Servo Amplifier Type	Analog Controller	

HS-77BB



1-03236

GENERAL SPECIFICATION

HS-77BB			
Control System	PWM		
Position Sensor Type	Contact Analog Potentiometer		
Motor Type	Cored Metal Brush		
Operating Voltage Range	4.8V	-	-
Voltage	4.8V	-	-
No Load Speed	0.18sec/60°	-	-
Stall Torque	4.4kgf·cm (61.1 oz-in)	-	-
Peak Efficiency Torque	0.9kgf·cm (12.5 oz-in)	-	-
Standing Current	8mA	-	-
No Load Running Current	250mA	-	-
Stall Current	-	-	-
Deadband	8µs	-	-
Operating Travel	Default: ±67.5°, Non-programmable / Pulse Width: 900~2100µs(Center:1500µs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	24AWG		
Dimensions	44.1mm x 23.0mm x 24.8mm (1.736inch x 0.906inch x 0.976inch)		
Weight	35.0g (1.235oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	5 Resin Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	24T(Ø6)		
IP-Rating	IP54		
Servo Amplifier Type	Analog Controller		

HS-5685MH



1-03237

GENERAL SPECIFICATION

HS-5685MH			
Control System	PWM		
Position Sensor Type	Contact Analog Potentiometer		
Motor Type	Cored Metal Brush		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.20sec/60°	0.17sec/60°
Stall Torque	-	11.3kgf·cm (156.9 oz-in)	12.9kgf·cm (179.1 oz-in)
Peak Efficiency Torque	-	2.3kgf·cm (31.9 oz-in)	2.6kgf·cm (36.1 oz-in)
Standing Current	-	6mA	7mA
No Load Running Current	-	280mA	350mA
Stall Current	-	2,100mA	2,600mA
Deadband	-	4μs	4μs
Operating Travel	Default: ±60°, Programmable: Max 175° / Pulse Width: 900~2100μs(Center:1500μs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	22AWG		
Dimensions	40.8mm x 20.0mm x 37.8mm (1.606inch x 0.787inch x 1.488inch)		
Weight	60.0g (2.116oz)		
Bearing Type	2 Ball Bearing		
Case Material	Engineering Plastic		
Gear Material	1 Metal-Plastic & 3 Metal Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	24T(Ø6)		
IP-Rating	IP4X		
Servo Amplifier Type	8bit Programmable Digital		

HS-5765MH

1-03238

**GENERAL SPECIFICATION**

HS-5765MH			
Control System	PWM		
Position Sensor Type	Contact Analog Potentiometer		
Motor Type	Cored Carbon Brush		
Operating Voltage Range	3.5 ~ 8.4V		
Voltage	-	6.0V	7.4V
No Load Speed	-	0.16sec/60°	0.13sec/60°
Stall Torque	-	20.0kgf-cm (277.7 oz-in)	25.0kgf-cm (347.2 oz-in)
Peak Efficiency Torque	-	4.0kgf-cm (55.5 oz-in)	5.0kgf-cm (69.4 oz-in)
Standing Current	-	3mA	3mA
No Load Running Current	-	840mA	1,100mA
Stall Current	-	4,700mA	5,800mA
Deadband	-	5μs	5μs
Operating Travel	Default: ±60°, Programmable: Max 175° / Pulse Width: 900~2100μs(Center:1500μs)		
Continuous Rotation	n/a		
Operating Temperature Range	-20°C ~ +60°C (-4°F ~+140°F)		
Storage Temperature Range	-30°C ~ +80°C (-22°F ~+176°F)		
Connector Wire Length	300mm (11.811inch)		
Connector Wire Gauge	22AWG		
Dimensions	59.0mm x 29.0mm x 52.0mm (2.323inch x 1.142inch x 2.047inch)		
Weight	172.3g (6.078oz)		
Bearing Type	3 Ball Bearing		
Case Material	Engineering plastic & Aluminum Heat Sink		
Gear Material	1 Metal-Plastic & 3 Metal Gears		
Gear Train Backlash	Max 0.5°		
Horn Gear Spline	15T(Ø8.0)		
IP-Rating	IP54		
Servo Amplifier Type	8bit Programmable Digital		



Anwendungsbeispiel für HiTEC-Servos

Hier im Roboter-Arm

Typical application for HiTEC servos –

here in a robot arm

CUSTOMER-SPECIFIC ADAPTATION

As a sister company of Hitec RCD Korea Inc., we are able to realize individual customer requests. The following adaptations/modifications are possible:

- Changes to cable type and length
- Changes to connectors
- Adaptations to accessories
- Adaptations to packaging (outer packaging and container size)
- Programming service
- Assembly service
- Extended outgoing goods inspection (test bench and logging)
- Label changes (Nameplate, serial number, etc.)
- Product adaptations (e.g., gear ratio)
- Fulfillment of special certification requirements
- Component tracing
- Special delivery agreements (blanket orders, guaranteed delivery capabilities)



Anwendungsbeispiel für HiTEC-Servos

Hier in einem Robotergetriebe

Typical application for HiTEC servos –

In this case in a robot gearbox

PROGRAMMING DEVICES

Hitec digital actuators offer the ability to adjust various settings and activate safety features. These parameters can be changed using various programming devices.

HFP-30

The Hitec HFP-30 offers extensive configuration options and test functions. Its compact dimensions make it ideal for mobile use, as it does not require a computer. The HFP-30 can be used to program all Hitec digital PWM actuators.



DPC-11

The Hitec DPC-11 is a cost-effective programming interface for use with a computer running Windows. All settings can be easily modified and optionally saved. This allows, for example, the selected settings to be easily archived or transferred to other servos. The connection is via USB.



DPC-CAN

The Hitec DPC-CAN interface allows you to configure, update, or test Hitec CAN and UAVCAN servos. Various software applications are available for this purpose. A computer with a Windows operating system is required. The connection is via USB.



25T($\varnothing 5,0$)


SERVO OUTPUT ARMS

A wide range of output arms is available for the entire Hitec servo portfolio.


Servos usually come with a selection of suitable output arms.

For special requests, you can choose from our wide range; please contact us.


MS-I25




MS-L25




MS-X25




MS-ML25

**24T ($\varnothing 6,0$)****15T($\varnothing 4,0$)**


FS-IL15




FS-IS15




FS-X15




HD-M15-L




FS-IXL15




M-I24




M-X24




M-O24




R-O24




R-I24




R-X24




R-C




R-D




HD-IL24




HD-IM24




HD-IS24




HD-LS24




R-XA24




SP-24



HD-IG24




HD-LL24



HD-LG24




HD-OS24





R-ML24












R-MO24




Q-MI24



H25T($\varnothing 6,0$)

**SQUARE10****SQUARE12****SQUARE4** / **SQUARE5**



MULTIPLEX Modellsport GmbH & Co.KG • Westliche Gewerbestr. 1 • D-75015 Bretten • Germany
 Tel. +(49) (0) 7252 58093-20 • Fax +(49) (0) 7252 58093-99 • www.multiplex-cs.de • salesteam@multiplex-cs.de

